

DUAL HEAD CORNERMATIC® CLASSIC


Cornermatic® automatically inserts and crimps specially designed TDC®/TDF® style corners in seconds. Lets you do a duct section, eight corners, in about 60 seconds with virtually no physical exertion. Compared to other methods of hand insertion and crimping, it's a saving of 3 to 6 minutes per section of ductwork depending on size and gauge.

- Corners are inserted square and fully crimped.
- No need to change the crimping adjustment when inserting corners in 18 to 26 gauge ducts.
- Each quick loading magazine holds up to 175 corners.
- Corners are shipped presorted and oriented for direct loading into the magazine.
- No need for hand sorting.
- Push the ductwork or fitting into the flange guides and the machine automatically does the rest.
- Rotate duct to each corner, then flip and repeat until all 8 corners are crimped.
- Handles 5' nominal duct

ADJUSTABLE DUAL HEAD CORNERMATIC® CLASSIC

Adjustable Dual Head Cornermatic® Classic adds the feature of automatically adjusting the upper crimping head to handle duct from 48" to 72" in length.

Model Details



MODEL	CAPACITY	DEPTH OF POCKET	OTHER
DUAL HEAD CORNERMATIC® CLASSIC & ADJUSTABLE DUAL HEAD CORNERMATIC® CLASSIC	18 to 26 (.050" to .022" / 1.3mm to 0.6mm) Mild Steel Only	Flange Type for insertion: TDC®/TDF® (Customer to Specify)	Model Capacity - Depends on strapped or boxed type corners used 16 gauge capacity available.
SPEED	AIR CONSUMPTION/MOTOR/VOLTAGE	DIMENSIONS/WEIGHT	
N/A	0.5 CU. ft/cycle @100 PSI	Length - 40" Width - 47" Height - 34" Weight - 1,100 lbs.	
N/A	N/A	Length - 34" Width - 8-1/2" Height - 4" Weight - 95 lbs.	
SPEED	MOTOR/VOLTAGE	DIMENSIONS/WEIGHT	
Approximately 2 ½ seconds per corner	Electrical - 110/1/60 (Single Phase) Air - 85 to 100 PSI (5.5 - 7 Bar)	Model CM3-DH: 24-1/8" x 24-1/8" x 116" Weight - 1,400 lbs. Model CM3-DHA - 35-3/4" x 35-3/4" x 127" Weight - 1,800 lbs.	