
PROFAB Manual Foot Rocker Spot Welder

PRODUCT DESCRIPTION

MODEL BSM226RF - 220 VOLT SINGLE PHASE

S1 Control

Simple dial controls for ease of use.

SPOTWELDER FEATURES:

- Foot-operated rocker arm resistance spotwelder (manual)
- Arms adjust 15" to 29"
- Uses standard Morse #1 tapered tips
- Water-cooled transformer, arms and tip holders
- 220 1PH electrics
- Dimensions: 40"L x 12"W x 50"H
- Weight: 300 lbs. (425 lbs. crated)
- 25 KVA Capacity: 2 pcs 14 gauge
- Custom lower arm design allows welding tubes as small as 2" diameter and no hoses to interfere with parts
- *Optional ProCool II coolant recirculator available (shown below)*



[PROFAB Spot Welder PX1600 Quick Start Up Guide \(pre 2020\)](#)

[PROFAB Spot Welder PX1700 Quick Start Up Guide \(2020\)](#)

[PROFAB Spot Welder Manual](#)

PROCOOL II COOLANT RECIRCULATOR FEATURES:

- Plastic water tank eliminates coolant contamination due to electrolysis or chemical reactions
- All units are plumbed with copper tubing and reinforced hose.
- New extended life pump features a direct drive power system reducing maintenance and vibration
- No external plumbing is required because of closed loop water system
- Self priming pump
- Easy change pump
- Strong rigid construction designed to support power unit
- Compact design
- Factory set at 50 psi adjustable to 80 psi
- 3 gallon reservoir
- Net weight: 37 lbs / 17 kg

The spot welder is now completely up and running, works perfectly. The electricians hook up the cooler to come on when I turn the welder on. Thanks for your assistance on this piece of equipment. I'm sure we will be ordering more shop toys soon.

P. Sturges-

Looking for a great alternative to the Pei Point spot welder? This is it!

*440v transformer can be added for additional cost. Call for details.

ADDITIONAL INFORMATION

Weight	425 lbs
Dimensions	40 × 12 × 50 in
Voltage	656, 657
Recirculator	None, ProCool II Coolant Recirculator
Manufacturer	Production Products, Inc.
Brand	PROFAB

VARIATIONS

PROFAB Spot Welder PX1600 Quick Start Up Guide (pre 2020)

PROFAB Spot Welder PX1700 Quick Start Up Guide (2020)

PROFAB Spot Welder Manual

PROCOOL II COOLANT RECIRCULATOR FEATURES:

- Plastic water tank eliminates coolant contamination due to electrolysis or chemical reactions
 - All units are plumbed with copper tubing and reinforced hose.
- New extended life pump features a direct drive power system reducing maintenance and vibration
 - No external plumbing is required because of closed loop water system
 - Self priming pump
 - Easy change pump
 - Strong rigid construction designed to support power unit
 - Compact design
 - Factory set at 50 psi adjustable to 80 psi
 - 3 gallon reservoir
 - Net weight: 37 lbs / 17 kg

The spot welder is now completely up and running, works perfectly. The electricians hook up the cooler to come on when I turn the welder on. Thanks for your assistance on this piece of equipment. I'm sure we will be ordering more shop toys soon.

P. Sturges-

Looking for a great alternative to the Pei Point spot welder? This is it!

*440v transformer can be added for additional cost. Call for details.

