



REF.#MSDSV1.0.DT.22.04.2024

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

- **Trade Name:** STYRENE MONOMER
- **CAS Number:** 100-42-5
- **Application of the substance/preparation:** Industrial use
- **Synonym:** Cinnamene, Ethenylbenzene, Phenylethene, Phenylene, Phenylethylene, Styrol, Styrolene, Vinylbenzene, Vinylbenzol, Vinyl benzene.
- **Contact:** Technical Manager
- **Website :** [www.shrashi.com](http://www.shrashi.com)

## SECTION 2: HAZARD(S) IDENTIFICATION

## 2.1 Classification of the substance or mixture

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	flammable liquid	3	Flam. Liq. 3	H226
3.1D	acute toxicity (dermal)	5	Acute Tox. 5	H313
3.1I	acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8R	specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
3.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
3.10	aspiration hazard	1	Asp. Tox. 1	H304
4.1A	hazardous to the aquatic environment - acute hazard	2	Aquatic Acute 2	H401
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

\*For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects  
Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses. Additional information. According to the results of its assessment, this substance is not a PBT or a vPvB.

## 2.2 Label elements

Labeling

- Signal word danger

- Pictograms

GHS02, GHS07, GHS08



**- Hazard statements**

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects. - Precautionary statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

**2.3 Other hazards**

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS****3.1 Substances**

Name of substance	Styrene Monomer
Identifiers	
CAS No	100-42-5
Molecular formula	C <sub>8</sub> H <sub>8</sub>
Molar mass	104.2 g/mol

**SECTION 4: FIRST-AID MEASURES****4.1 Description of first-aid measures**General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Following inhalation

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

**Following skin contact:** Wash with plenty of soap and water.

**Following eye contact:** Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

**Following ingestion:** Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms and effects are not known to date.

**4.3 Indication of any immediate medical attention and special treatment needed**

none

**SECTION 5: FIRE-FIGHTING MEASURES****5.1 Extinguishing media**

Suitable extinguishing media: Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : Water jet

**5.2 Special hazards arising from the substance or mixture**

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products : Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

**6.3 Methods and material for containment and cleaning up**

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite),

Sand, Universal binder Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

**6.4 Reference to other sections**

Hazardous combustion products: see section 5.

Personal precautions: see section 8.

Incompatible materials: see section 10.

Disposal considerations: see section 13

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling**

## Recommendations

- Measures to prevent fire as well as aerosol and dust generation  
Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

## - Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

## Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feeding stuffs.

**7.2 Conditions for safe storage, including any incompatibilities**

## Managing of associated risks

## - Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

## - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight. - Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

## - Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

**7.3 Specific end use(s)**

See section 16 for a general overview.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters**

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
MX	styrene	100-42-5	VLE		20	40		NOM-010STPS

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

**Human health values**

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	85 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	289 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	306 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
DNEL	406 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

**Environment values**

Relevant PNECs and other threshold levels				
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0.04 mg/l	aquatic organisms	water	intermittent release
PNEC	0.028 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0.014 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	5 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0.614 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0.307 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0.2 mg/kg	terrestrial organisms	soil	short-term (single instance)

**8.2 Exposure controls**

Appropriate engineering controls  
General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leaktightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures



Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

#### Appearance:

**Physical state**

Liquid

**Color**

Colourless

**Odor**

Sweet aroma

#### Other safety parameters:

**pH (value)**

not determined

**Melting point/freezing point**

-31 °C

**Initial boiling point and boiling range**

145 °C at 1,013 hPa

**Flash point**

31 °C at 1,013 hPa

**Evaporation rate**

not determined

**Flammability (solid, gas)**

not relevant (fluid)

#### Explosive limits:

- Lower explosion limit (LEL)

0.9 vol%

- Upper explosion limit (UEL)

6.1 vol%

Vapor pressure

6.67 hPa at 20 °C

Density

not determined

Vapor density

this information is not available

Relative density

information on this property is not available

Solubility(ies)

- Water solubility

320 mg/l at 25 °C

Partition coefficient

- n-octanol/water (log KOW)

2.96 (25 °C) (ECHA)

- Soil organic carbon/water (log KOC)

2.547 (ECHA)

Auto-ignition temperature

490 °C

Viscosity

not determined

Explosive properties

none

Oxidizing properties

none



## 9.2 Other information

Temperature class (USA, acc. to NEC 500)

T1 (maximum permissible surface temperature on the equipment: 450°C)

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". It's a reactive substance. The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

### 10.2 Chemical stability

Non-stabilized styrene can polymerize at room temperature in the presence of light with an exothermic and violent reaction to solid polystyrene. Above 95 degrees C the reaction is self-heating and may explode. The initiators of the polymerization, like rust and lyes, accelerate the reaction. In the distillation leave residue in the flask and do not overheat due to danger of explosion! Risk of explosion on contact with: oxygen, strong acids, hydroperoxides, peroxides, polymerization accelerators (light, Pressure, heat).

Risk of explosion when storage temperatures exceed 32 degrees Celsius.

The substance polymerizes in contact with: sodium, aluminum trichloride, azoisobutyronitrile,

The substance may react dangerously with: oxidizing agents, butyllithium, chlorine / iron catalyst, chlorosulfuric acid / Enclosure, Oleum, Heat / steam, Xenon tetrafluoride.

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects Classification acc. to GHS

Acute toxicity

May be harmful in contact with skin. Harmful if inhaled.

- Acute toxicity estimate (ATE)

Dermal 2,500 mg/kg

Inhalation: vapor 11 mg/l/4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

**Carcinogenicity**

Shall not be classified as carcinogenic.

**Reproductive toxicity**

Shall not be classified as a reproductive toxicant. Specific target organ toxicity - single exposure May cause respiratory irritation.

**Specific target organ toxicity - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity**

Toxic to aquatic life with long lasting effects.

**Aquatic toxicity (acute)**

Endpoint	Value	Species	Exposure time
LC50	10 mg/l	fish	96 h
EC50	3.32 mg/l	fish	96 h
ErC50	4.9 mg/l	algae	72 h

**Aquatic toxicity (chronic)**

Endpoint	Value	Species	Exposure time
EC50	1.88 mg/l	aquatic invertebrates	21 d
LC50	>3.84 mg/l	aquatic invertebrates	21 d

**12.2 Persistence and degradability****Process of degradability**

Process	Degradation rate	Time
carbon dioxide generation	>50 %	33 d

**12.3 Bioaccumulative potential**

Data are not available.

n-octanol/water (log KOW)

2.96 (25 °C) (ECHA)

BCF

74 (ECHA)

**12.4 Mobility in soil**

Data are not available.

Henry's law constant

231.6 Pa m<sup>3</sup>/mol

The Organic Carbon normalised adsorption coefficient

2.547 (ECHA)





**12.5 Results of PBT and vPvB assessment**

Data are not available.

**12.6 Other adverse effects**

Data are not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

Waste treatment-relevant information  
Solvent reclamation/regeneration.

Sewage disposal-relevant information  
Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets. Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**SECTION 14: TRANSPORT INFORMATION**

**14.1 UN number**

2055

**14.2 UN proper shipping name**

STYRENE MONOMER, STABILIZED

**14.3 Transport hazard class(es)**

Class

3 (flammable liquids)

**14.4 Packing group**

III (substance presenting low danger)

**14.5 Environmental hazards**

non-environmentally hazardous acc. to the dangerous goods regulations

**14.6 Special precautions for user**

There is no additional information.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**

The cargo is not intended to be carried in bulk.

**Information for each of the UN Model Regulations**

**Transport information - National regulations - Additional information (UN RTDG)**

UN number	2055
Proper shipping name	STYRENE MONOMER, STABILIZED
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	386 (UN RTDG)
Excepted quantities (EQ)	E1 (UN RTDG)
Limited quantities (LQ)	5 L (UN RTDG)



**International Maritime Dangerous Goods Code (IMDG)**

UN number	2055
Proper shipping name	STYRENE MONOMER, STABILIZED
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	386
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	C

**International Civil Aviation Organization (ICAO-IATA/DGR)**

UN number	2055
Proper shipping name	Styrene monomer, stabilized
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	A209
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations specific for the product in question**

There is no additional information.

**National regulations (United States) Toxic Substance Control Act (TSCA)** substance is listed  
**SARA TITLE III (Superfund Amendment and Reauthorization Act)**

- List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304) not listed
- Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313)

**Toxics Release Inventory: Specific Toxic Chemical Listings**

Name acc. to inventory	CAS No	Remarks	Effective date
styrene	100-42-5		1986-12-31

**CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)**

**- Section 102(A) Hazardous Substances (40 CFR 302.4)**

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
Styrene Monomer	100-42-5		1 3	1000 (454)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act 3  
"3" indicates that the source is section 112 of the Clean Air Act. Clean Air Act not listed



New Jersey Worker and Community Right to Know Act N.J.S.A. 34:5A-1 et. seq.

Right to Know Hazardous Substance		List	
Name acc. to inventory	CAS No	Remarks	Classifications
STYRENE MONOMER (BENZENE, ETHENYL-, PHENYLETHYLENE)	100-42-5		CA F3 R2

**Legend**

CA Carcinogenic

F3 Flammable - Third Degree

R2 Reactive - Second Degree

**California Environmental Protection Agency (Cal/EPA): Proposition 65 Chemicals known to the State to cause cancer or reproductive toxicity**

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
styrene	100-42-5		cancer

**15.2 Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out for this substance.

**SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION****Abbreviations and acronyms**

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NOM-010-STPS	NORMA Oficial Mexicana NOM-010-STPS: Agentes químicos contaminantes del ambiente laboral-Reconocimiento, evaluación y control
PBT	Persistent, Bioaccumulative and Toxic



PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
VLE	Permissible exposure limit
vPvB	Very Persistent and very Bioaccumulative

**Key literature references and sources for data**

Norma Oficial Mexicana NOM-018-STPS-2015, Sistema armonizado para la identificación y comunicación de peligros y riesgos por sustancias químicas peligrosas en los centros de trabajo y NMX-R-019-SCFI-2011 Sistema Armonizado de Clasificación y Comunicación de Peligros de los Productos Químicos.

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

**List of relevant phrases (code and full text as stated in chapter 2 and 3)**

Code	Text
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

**Disclaimer:** The information contained in this safety data sheet, as of the issue date, is believed to be true and correct. However, the accuracy or completeness of this information and any recommendations or suggestions are made without warranty or guarantee. Since the conditions of use are beyond the control of our company, the company has no liability for damages suffered by the purchaser or other persons in handling of these materials and it is the sole responsibility of the user to determine the conditions of safe use of this preparation. The information in this sheet does not represent analytical specifications, for which please refer to our Technical Data Sheet.