

All PAC steel strapping is manufactured in the United States to ASTM specification #D3953-05. PAC steel strapping is consistent in width, gauge and finish. Published break strengths are average and meet, or exceed, industry standards. PAC stocks both regular duty and high tensile at several locations. In addition to the stock sizes listed, we can also supply specialty products on request.

Regular Duty Steel Strapping

Regular duty steel strapping is manufactured from cold rolled steel. All PAC regular duty steel can be used in manual and pneumatic tools, as well as automatic steel strapping heads.

High Tensile Steel Strapping

High tensile steel strapping is manufactured from cold rolled steel and heat treated to maximize break strength and ductility. High tensile steel provides additional break strength and shock resistance for your toughest applications.

Stock Steel Strapping

PRODUCT	COIL WIDTH (inches)	THICKNESS (inches)	AVERAGE BREAK (lbs.)	YIELD (ft./lb.)	AVERAGE COIL WEIGHT (lbs.)	COILS PER PALLET
Oscillated Wound, Regular Duty Steel						
3/8 x .015	3/8	.015	665	52.29	80	12
1/2 x .015	1/2	.015	890	39.22	100	12
1/2 x .020	1/2	.020	1180	29.42	100	12
1/2 x .023	1/2	.023	1350	25.58	100	12
5/8 x .020	5/8	.020	1470	23.53	100	12
5/8 x .023	5/8	.023	1690	20.46	100	12
3/4 x .020	3/4	.020	1765	19.61	100	12
3/4 x .023	3/4	.023	2025	17.05	100	12
Oscillated Wound, High Tensile Steel						
1/2 x .020HT	1/2	.020	1485	29.42	100	12
5/8 x .020HT	5/8	.020	1855	23.53	100	12
5/8 x .023HT	5/8	.023	2130	20.46	100	12
3/4 x .025HT	3/4	.025	2770	15.69	100	12
3/4 x .029HT	3/4	.029	3205	13.30	100	12
Ribbon Wound, High Tensile Steel						
11/4 x .029HT	11/4	.029	5530	8.11	100	20

Standard finish on PAC steel strapping is black, painted and waxed. Alternative finishes are available on request.
Steel strapping is sold by the hundred weight in full pallet quantities only.

Portable Coils

Steel portable coils are used in a variety of applications where a full coil of steel is not needed or is not practical. All portable coils are ribbon wound in a self-dispensing carton.

PRODUCT	COIL LENGTH (feet)	STRAP WIDTH (inches)	STRAP THICKNESS (inches)	AVERAGE BREAK (lbs.)	WEIGHT (lbs.)
Regular Duty Portable Coils					
3/8 x .015-300	300	3/8	.015	665	6
1/2 x .015-300	300	1/2	.015	890	8
1/2 x .020-300	300	1/2	.020	1180	10
1/2 x .023-300	300	1/2	.023	1350	11
5/8 x .015-300	300	5/8	.015	1125	10
5/8 x .020-300	300	5/8	.020	1470	13
5/8 x .023-300	300	5/8	.023	1690	14
3/4 x .015-300	300	3/4	.015	1350	12
3/4 x .020-300	300	3/4	.020	1765	15
3/4 x .023-300	300	3/4	.023	2025	18
High Tensile Portable Coils					
1/2 x .020HT-300	300	1/2	.020	1485	10
5/8 x .020HT-300	300	5/8	.020	1855	13
5/8 x .023HT-300	300	5/8	.023	2130	14
3/4 x .025HT-280	280	3/4	.025	2770	19
3/4 x .029HT-200	200	3/4	.029	3205	22