

Method Jelly

Submission Date	
Name of Firm	
Project name	

Architectural Specification

Method Jelly is an RGBW performance safety fixture. Jelly shall consume a maximum of 125mA at 24VDC. Jelly shall be powder-coated black and offer an acrylic diffusion lens. Jelly shall be designed to mount on standard single-gang boxes. Jelly shall be designed to wire in parallel to other Method fixtures as designed by Method.

Jelly has individual control over Red, Blue, Green, and White (40k) LED diode

Jelly control shall be achieved via constant voltage current LED dimming drivers. Controller shall have DMX input, DMX loop-thru, 0-10v, and contact closure control capabilities. A maximum of 16 Jellys may be connected to a single 240-watt, 24VDC power supply utilizing 14-gauge stranded wire with a total wire run of no more than 350 feet. A standard 6-channel Method control card may be used to control up to 35 fixtures per channel with control via DMX or analog slider operation through a highest-takes-precedent protocol.

Power supplies shall be switching power supplies for maximum system efficiency with power consumption of less than 15 watts at 120VAC when the system is idle. Control cards shall be six-circuit cards capable of controlling up to 6000mA per circuit. Power supplies and control cards are optional if other control methods are to be used. Consult factor for options that include vented NEMA enclosures with DIN mounted power supplies and control cards.



Ordering Information

	Fixtures Total	
	Zone Total	
	Zone 1:	
	Zone 2:	
	Zone 3:	
	Zone 4:	
	Zone 5:	
	Zone 6:	

Power Supply

Blank - No Supply 24 - 240-watt 24VDC

48 - 480-watt 24VDC

LV - 120VAC dimmed via magnetic

transformer

Mounting

S - Surface Mount

Accessories

F - Frosted Lens

Control

ND - Non Dim Switching DMX - DMX Controls By Others DMX-S - Single Slider Control

DMX-D - Double Slider Control

Warranty

Warranty: Fixture carries a two year limited warranty. Fixtures wired to non-Method power supplies will not be covered. Fixtures installed in a manner unintended for use will not be covered.

Example Part Number

MP-	24-	120-	10-	F-	DMX-S	
Model	Watts	Voltage	Quanity	Accessories	Control	