



Slingshade Flag Mount Installation Instructions

Thank you for your support! These mounts were designed to mount to the inner lower openings of your roll hoops to provide the **FIRST** available flag mount option for the Polaris Slingshade®. These support a 6"x9" flag (sleeve style)(sold separately) and are hand made entirely of steel for unrivaled durability. The shaft of the poles are lined with rubber to offer protection for your flag and will provide years of joy flying your flags.

Package Contents (Set):



- 2 Flag Poles with Mounts
- 2 ¼ 20 Acorn Nuts
- 2 ¼ 20 Hex Nuts
- 4 Mounting Plates
- 2 2.75" Extension Brackets
- 2 6mm x 1¹¹/₁₆" All Thread
- 4 M6 x 20mm Socket Head Cap Screws (5mm Drive)
- 2 M6 x 10mm Socket Head Cap Screws (5mm Drive)(For Flag Poles)
- 2 M6 Flange Nuts
- 2 M6 Couplers
- 4 M6 Flat Washers
- 4 M6 Split Lock Washers
- 6 M6 Acorn Nuts

1. Align mounting plates (front & rear) in lower inner roll hoop and place M6 x 20mm cap screw into upper mounting hole from the front side.
2. Using one M6 acorn nut, hand tighten onto the M6 x 20mm cap screw to hold plate in place.
3. Place additional M6 x 20mm cap screw into lower mounting hole from the front side.
4. Place one M6 flat washer on M6 x 20mm cap screw from the rear side.
5. Place preassembled all thread assembly on the M6 x 20mm cap screw.
6. Adjust mounting plates for proper positioning and tighten down both mounting screws with a 5mm allen key.

Note: Steps 7-8 completed prior to shipping.

7. Using one M6 flange nut, thread onto all thread with flange facing the rear until nut meets rubber coating.
8. Thread all thread into coupler until rubber coating meets coupler.
9. Place one M6 split lock washer on all thread.
10. Place the rounded end of one of the 2.75" extension brackets onto the all thread.
11. Place one M6 flat washer & M6 split lock washer onto all thread.
12. Ensuring the 2.75" extension bracket is level, place M6 acorn nut onto all thread and tighten down.
13. Place one M6 x 10mm screws through flag mount; ensure 90° angle bracket of flag mount is facing towards the rear.
14. Place flag mount assembly and M6 x 10mm screw through other end of the 2.75" extension bracket.
15. Keeping flag pole straight, use one M6 acorn nut and tighten down the M6 x 10mm screw.
16. Slip flag onto pole and reinstall ¼ 20 nut and acorn nut; tighten acorn nut to hex nut using 7/16th wrench.
 - Prior to installing ¼ 20 nut and acorn nut, check upper sleeve of flag to ensure it is unable to slip over nut. If so, use thread to decrease sleeve hole on flag.
17. Repeat on other side (if applicable).
18. Enjoy!

Congratulations, you have just installed your Flag Mounts. My goal is to provide a superior product to the Slingshot Community and all feedback is appreciated. Please feel free to reach out to me directly with any issues or concerns via phone call, text message, or e-mail. Thank you again for supporting DS Designs.