



Belt Conveyors


SPECIFICATIONS

	5"	8"	10"	15"
Belt Width	5"	8"	10"	15"
Cleat Height	2" on 8" Centers	2" on 8" Centers	2-1/2" on 8" Centers	3" on 8" Centers
Standard Temp Range	0-180° F	0-180° F	0-180° F	0-180° F
Belt Speed	272 FPM	272 FPM	289 FPM	272 FPM
Capacity @ 40° Incline	589 BPH	943 BPH	1565 BPH	2652 BPH
Capacity @ Horizontal	733 BPH	1173 BPH	1931 BPH	3273 BPH
Drive Pulley	6-1/2" Crowned w 1/4"	Lagging	8-1/2" Crowned w 1/4" Lagging	10-1/2" Crowned w 1/4" Lagging
11'	2hp	3hp	3hp	3hp
15'	2hp	3hp	3hp	5hp
19'	2hp	3hp	3hp	5hp
23'	3hp	3hp	3hp	5hp
27'	3hp	3hp	3hp	5hp
31'	3hp	5hp	5hp	7.5hp
35'	5hp	5hp	5hp	7.5hp
39'	5hp	5hp	5hp	7.5hp
43'	5hp	5hp	5hp	7.5hp
19' w/Chassis	2hp	3hp	3hp	5hp
27' w/Chassis	3hp	3hp	3hp	5hp
35' w/Chassis	5hp	5hp	5hp	7.5hp
43' w/Chassis	5hp	5hp	5hp	7.5hp

Horsepower required for length.


CONVEYOR REACH & ELEVATION @ 40°

	19'	27'	35'	43'
A	19'	27'	35'	43'
B	11'1"	16'9"	21'6"	26'4"
C	4'	5'6"	10'	12'11"
D	10'1"	15'3"	16'3"	20'




CROSS SECTION DIMENSIONS

	A	B	C	D
5"	11-9/16"	5-1/16"	2-1/2"	8-7/32"
8"	11-9/16"	8-1/16"	2-1/2"	11-7/32"
10"	14-11/32"	10-1/16"	3"	13-7/32"
15"	17-17/32"	15-1/16"	3-1/2"	18-7/32"




Belt Conveyors



Belt custom-fitted at the factory for less seed damage and loss.



- Polymer rollers on chassis units for easy height adjustment. Powdercoat and galvanized finish provides tough corrosion protection.



Heavy duty winch with automatic brake for raising and lowering conveyor.



Automotive grade fasteners and precision laser cut parts ensure easy assembly and repair.




Generous 34" x 24" bulk bag hopper is standard on chassis models, low profile hopper also available.



Rugged hitch makes transporting simple and safe.


Belt Conveyors




Generous discharge opening with rubber-backed end plate minimizes clogs and seed damage



Block and pulley lift system makes raising and lowering an easy task on chassis units. Galvanized chassis lasts for years of service.



Heavy duty adjustable motor mount allows for most standard drive motors.



Durable cleats for fast and gentle material flow.



Tapered bearing spindles on axles and optional trailer rated tires allow for worry free transport.