

2026 Riverside International Speedway Crown Vic Rules

CROWN VIC/GRAND MARQUIS

BODY

Front and Rear Bumper must remain stock with NO sharp edges. Bumpers must have tow chains front and rear. May have hoop with two support braces to protect radiator. No outside frame support.

No push bars on the front or rear of the car.

Hood and trunk may utilize stock hinges but must be secured with hood pins.

No hulling or lightening of body. The only areas on the car that may be hulled are the front driver and passenger doors.

All flammable materials and glass must be removed.

Any holes in the front firewall and rear firewall must be covered with aluminum or steel.

All cars must have numbers on the front doors and roof.

The steering column must remain stock, all airbags must be removed. Quick Release Steering Wheel OK but must be mounted on stock steering column.

Must have at least four (4) vertical windshield bars in front of driver

Roll cage must be inside driver compartment only, **NO part of cage may extend outside of driver compartment.**

Four (4) driver door bars and three (3) passenger door bars minimum.
Cage must be securely mounted to frame.

Suspension

No altering of stock suspension.

Engine/Transmission

Engine must be completely stock.

4.6 SOHC

Must have mufflers.

Exhaust must exit behind driver.

Catalytic converter may be removed.

Transmission must be completely stock.

The A.C. condenser must be removed.

SAFETY

Drivers must wear full fire suit, racing gloves, racing shoes and helmet while on track.

Han's device recommended.

Racing seat and belts mandatory.

Racing belts must have five (5) point system.

Fire extinguisher required in all cars.

TIRES/WHEELS

Tires must be DOT legal, and all four (4) tires must be the same size.

Wheels must be stock steel and all four (4) wheels must be same size and offset.

No wheel spacers of any kind.

WEIGHT

No adding ballast of any type to car.

BRAKES

Must remain factory stock, all four (4) corners must be operable.

REAR-END

Must be factory stock rear-end with stock components.

The only legal gears will be 2.73, 3.27 and 3.55.

Rear differential may be locked by any means necessary, but gear ratio rule remains the same (3.55 max gear).

FUEL

Pump gas only! **NO RACING FUEL!**

Stock fuel tank and fuel pump only.

THE ABSENCE OF A SPECIFIC RULE DOES NOT IMPLY APPROVAL, CONSET OR PERMISSION REGARDING THAT SUBJECT. ANY QUESTIONS OR DOUBTS ABOUT SUCH MATTERS SHOULD BE DIRECTED TO RACETRACK OFFICIALS FOR CLARIFICATION.