

DEN-CRIB-GOLD

This CRIB Premium is Suitable for apartment with 5+BHK.

Intrusion Alarm Kit - WIRELESS



25 zones, 16 zones programmable as delay, immediate, panic, fire, part and staff, 8 zones dedicated for wireless key-fobs & wireless panic switches, 1 dedicated tamper zone, Secure code hopping technology, Onboard 16 button keypad, 4 line back lit LCD display, Automatic arming and disarming at pre-programmed times, Two user codes – master and staff,

Part and Full arm modes for convenient daily use, Power failure, blown fuse, low battery indication on LCD display, Open zones are indicated on LCD display, Independent entry and exit delay times programmable from 2 to 255 seconds, Programmable sounder time from 2 to 20 minutes.

TECHNICAL SPECIFICATION:

ELECTRICAL

Quiescent current : 60mA
 Maximum current at internal sounder : 500mA
 Maximum sounder HT1 current output : 1A
 Sounder Saturation Voltage : <1V at 700mA

POWER SUPPLY

Mains supply Voltage : 220+10%-15% 50Hz
 Total current Output: 1000mA at 220 V AC
 Battery Voltage : 11.1 V DC
 Battery type : Lithium ion Rechargeable
 Battery Recharge Voltage: 12.4 V +/-0.2 V DC
 Fuse : 1000mA 20mm and 1000mA for sounder and Auxiliary Supply

ENVIRONMENTAL

Operating Temperature: 0C to 45C
 Storage Temperature: -20C to 60C
 Maximum humidity: 95% non-condensing
 Environment : residential / commercial / light Industrial

PHYSICAL

Dimensions : 230mm x 170mm x 50mm
 Max Battery Dimensions : 150mm x 110mm x 64mm



WIRELESS PIR MOTION SENSOR

Microcontroller based, Secure code hopping technology, Uses nanowatt technology, Easy learning based configuration with control panel, Dual element pyroelectric sensor, Digital Signal Processor (DSP), Detection range up to 10m, Sealed optics, Walk test / Transmit LED, Low battery alert to control panel, Periodic health notification, Inbuilt tamper switch, Long lasting lithium battery, Sleek ABS Housing.

TECHNICAL SPECIFICATION:

Detection method Passive infrared and Microwave
 Coverage 12m x 12m(40ft x 40ft) 85°wide
 Detection zones 78 zones
 Mounting height 1.5 to 2.4m (5 to 8ft)
 LED alarm indicator Switchable ON/OFF
 Tamper switch N.C., Open when cover is removed.
 PIR sensitivity/range Switchable LOW/MID/HI

Warm up period Instant
 Power input 3.3Volt
 Current consumption 20µA (normal), 19mA (max.) at 3.3V DC
 Dimensions 89mm x 52mm x 39mm (with bracket)
 Weight Approx. 110 g (with bracket: 130 g)
 Operating temperature -20°C to +55°C
 Environmental humidity 95% max.
 RF interference No alarm 10V/m



WIRELESS MAGNETIC CONTACT

Microcontroller based, Secure code hopping technology, Uses nano watt technology, Easy learning based configuration with control panel, Opening gap 15mm (maximum), Open and close transmission, Transmit LED, Low battery alert to control panel, Periodic health notification, Inbuilt tamper switch, Long lasting lithium battery, Sleek ABS Housing.

FEATURES:

Microcontroller based, Secure code hopping technology
Uses nano watt technology, Easy learning based configuration with control panel
Opening gap 15mm (maximum), Open and close transmission, Transmit LED



SMART SENSOR

DENLOB's smart sensor is a stand-alone external PIR motion sensor with sensitivity, time, Lux, retrigger & bypass controls. Suitable for indoor and outdoor installation. Can switch up to 1000W electrical load. Security Device, Welcome Light, and Energy Saving Device.

Smart sensors turn on lights, fans, air conditioners, or any other electric device whenever any motion is detected in their coverage area and automatically turns them off when there is no motion

Stand Alone External PIR Motion Sensor with sensitivity, time, Lux, retrigger & bypass controls & Can switch up to 1000W electrical load



STANDALONE GAS LEAKAGE SENSOR

Stand alone 220V AC Gas leak detector to detect leakage of liquid petroleum gas and compressed natural gas. Inbuilt alarm buzzer.

FEATURES:

Stand alone 220V AC Gas leak detector to detect leakage of liquid petroleum gas and compressed natural gas.
Inbuilt alarm buzzer.



SOUNDER 12V

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

- High power 130 db
- Police Siren Sound
- Suitable for Indoor and Outdoor application
- Tamper Loop
- Two sound speed options available
- white ABS Housing.



VIDEO DOOR PHONE - ANALOGUE

DENLOB's Video Door Phone is a 7-inch color TFT Screen in sleek ABS housing. It comes with an Outdoor station in a sturdy aluminium die-cast enclosure, can connect 2 additional monitors and 1 additional outdoor station, one CCTV camera can be connected per monitor, 6 capacitive touch buttons, Hands-free operation, door unlock function from indoor monitors, simple wire connection, ringtone volume, brightness, and contrast can be adjusted.

Features:

- 7 inch color TFT Screen in sleek ABS housing.
- Outdoor station in sturdy aluminium die cast enclosure.
- Can connect 2 additional monitors and 1 additional outdoor station.
- One CCTV camera can be connected per monitor.
- 6 capacitive touch buttons. Door unlock function from indoor monitors

Intrusion alarm Kit Includes			
SI	Product	Description	Quantity
1	Intrusion Control Panel-Wireless	Wireless 25 Zone Control Panel with Onboard Key Pad	1
2	PIR Motion Sensor- Wireless	Wireless PIR Motion Sensor with Intelligent Pet Immunity	4
3	Magnetic Contact-Wireless	Wireless Microcontroller based Dual Technology Sensor	8
4	Sounder	High power 130 db, Police Siren Sound	2
5	Smart Sensor	Standalone SMART SENSOR	1
6	GAS Leak Sensor	Standalone Gas Leak Detectors	1
7	Video Door Phone	VIDEO DOOR PHONE 7" HEXA	1
8	Additional Monitor	ADDITIONAL MONITOR FOR HEXA VDP	2
9	Additional Outdoor Camera	ADDITIONAL CAMERA FOR HEXA VDP	1

Please Note: Product Specification and Model can be Changed without any Prior Notice