DEN-CRIB-LITE



DEN-CRIB-LITE

This CRIB Lite is Suitable for apartment with 2+BHK

Intrusion Alarm Kit



TECHNICAL SPECIFICATION:

ELECTRICAL

Quiescent current: 75ma typical with all LED's and internal buzzer on Maximum sounder current output: 1A Maximum Strobe light current output: 1A Sounder and strobe saturation Voltage: <1V at 1A Remote keypads: five (max) Non volatile Memory: Programming and Log Zone response time: <500mS Zone Loop Resistance: <5kohm for Normally Closed

ENVIRONMENTAL

Operating Temperature: 0C to 45C Storage Temperature: -20C to 60C Maximum humidity: 95% non -condensing Environment: residential / commercial / light Indus trial



FEATURES:

- Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity.
- Detection Range 12m
- Multi Angle wall bracket.
- · ABS Housing.

12 Zone Control Panel with Onboard Key Pad and Automatic Arming & Disarming, 10 programmable zones, can Connect Separate Remote Key Pads, Inbuilt Power Supply.

Feature:

12 Zone Control Panel with Onboard Key Pad.Automatic Arming & Disarming.10 programmable zones.Can Connect Separate Remote Key Pads.Inbuilt Power Supply.

POWER SUPPLY

Mains supply Voltage: 220+10% -15% 50Hz Total current Output: 800MA at 220V AC (Fuse JA 20mm On Main Card) Regulation: <9% Ripple: <200mv RMS Battery VOLTAGE: 12V DC Battery type: SMF Rechargeable Battery Recharge voltage: 13.8V +/-0.2V DC Fuse: 250ma 20mm AC Mains on Power Supply Card

PHYSICAL

Dimensions: 236 mm x 226mm x 80mm Max Battery Dimensions: 150mm x 110mm x 64 mm

QUAD P.I.R. MOTION SENSOR

Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity. Detection Range 12m, Multi Angle wall bracket. ABS Housing.

TECHNICAL SPECIFICATION:

Detection method Passive infrared Coverage 12m x 12m(40ft x 40ft) 85° wide Detection zones 78 zones Mounting height 1.5 to 2.4m (5 to 8ft) LED alarm indicator Switchable ON/OFF Alarm period Approx. 2.5 sec Alarm output N.C., 24VDC 0.2A max. Tamper switch N.C., Open when cover is removed. Tamper output 24VDC 0.1A max. PIR sensitivity/range Switchable LOW/MID/HI Warm up period Approx. 30 sec Power input 9.5 to 16VDC Current consumption 8mA (normal), 11mA (max.) at 12VDC Dimensions H93.4mm x W61.4mm x D46.0mm Weight Approx. 70 g (with bracket: 90 g) Operating temperature -20°C to +50°C (-4°F to +122°F) Environmental humidity 95% max. RF interference No alarm 10V/m

DEN-CRIB-LITE





2wire MAGNETIC CONTACT

Opening Gap 12-15mm, with mounting holes in collar for ease of installation. ABS Housing. Colour options – white and black

Features:

Opening Gap 12-15mm With mounting holes in collar for ease of installation. ABS Housing. Colour options – white and black.



GAS Leak Sensor

Gas leak detector to detect leakage of liquid petroleum gas and compressed natural gas.

Features:

Gas leak detector to detect leakage of liquid petroleum gas and compressed natural gas.



SOUNDER 12V

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

High power 130 db Police Siren Sound Suitable for Indoor and Outdoor application Tamper Loop Two sound speed options available white ABS Housing.

VIDEO DOOR PHONE - ANALOGUE

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

High power 130 db Police Siren Sound Suitable for Indoor and Outdoor application Tamper Loop Two sound speed options available white ABS Housing.

DEN-CRIB-LITE



	Intrusion alarm & Video Door Phone Kit Includes		
SI	Product	Description	Quantity
1	Intrusion Control Panel-Wired	12 Zone Control Panel with Onboard Key Pad	1
2	PIR Motion Sensor	PIR Motion Sensor with Intelligent Pet Immunity	2
3	Siren	High power 130 db, Police Siren Sound	1
4	Door Sensor	MAGNETIC CONTACT 2 WIRE with Collar	3
5	Gas Leak Detector	Gas Leak Detectors	1
6	Video Door Phone- Wired	7" TFT screen Analogue Video Door Phone	1

Please Note: Product Specification and Model can be Changed without any Prior Notice