DEN-INTRUSION-KIT-01



DEN-INTRUSION-KIT-01

For Apartments or Medium Sized Villas

Intrusion Alarm Kit



TECHNICAL SPECIFICATION:

ELECTRICAL

Quiescent current: 75ma typical with all LED's and internal buzzer on Maximum sounder current output: 1A Maximum Strobe light current output: 1A Sounder and strobe saturation Voltage: <1V at 1A Remote keypads: five (max) Non volatile Memory: Programming and Log Zone response time: <500mS Zone Loop Resistance: <5kohm for Normally Closed

ENVIRONMENTAL

Operating Temperature: 0C to 45C Storage Temperature: -20C to 60C Maximum humidity: 95% non -condensing Environment: residential / commercial / light Indus trial



Feature:

12 Zone Control Panel with Onboard Key Pad.Automatic Arming & Disarming.10 programmable zones.Can Connect Separate Remote Key Pads.Inbuilt Power Supply.

POWER SUPPLY

Mains supply Voltage: 220+10% -15% 50Hz Total current Output: 800MA at 220V AC (Fuse JA 20mm On Main Card) Regulation: <9% Ripple: <200mv RMS Battery VOLTAGE: 12V DC Battery type: SMF Rechargeable Battery Recharge voltage: 13.8V +/-0.2V DC Fuse: 250ma 20mm AC Mains on Power Supply Card

PHYSICAL

Dimensions: 236 mm x 226mm x 80mm Max Battery Dimensions: 150mm x 110mm x 64 mm



FEATURES:

- Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity.
- Detection Range 12m
- Multi Angle wall bracket.
- ABS Housing.

QUAD P.I.R. MOTION SENSOR

Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity. Detection Range 12m, Multi Angle wall bracket. ABS Housing.

TECHNICAL SPECIFICATION:

Detection method Passive infrared Coverage 12m x 12m(40ft x 40ft) 85° wide Detection zones 78 zones Mounting height 1.5 to 2.4m (5 to 8ft) LED alarm indicator Switchable ON/OFF Alarm period Approx. 2.5 sec Alarm output N.C., 24VDC 0.2A max.

DEN-INTRUSION-KIT-01



DUAL TECH MAGNETIC CONTACT

Microcontroller based Dual Technology Magnetic Contact with inbuilt Digital Multi Function Detector. Magnetic Contact Opening Gap 12-15mm. Inbuilt Digital Multi Function Detector. Detects vibration, breaking off glass, cutting off aluminium frames or grills.

Features:

Microcontroller based Dual Technology Magnetic Contact with inbuilt Digital Multi Function Detector. Magnetic Contact Opening Gap 12-15mm. Inbuilt Digital Multi Function Detector. Detects vibration Breaking of glass Cutting off aluminium frames or grills.



METAL SHUTTER CONTACT

Metal housing, material aluminium alloy, 2 wire , contact rating 10W, Opening gap 50 – 60mm.

Features:

Metal housing Material aluminium alloy 2 wire Contact rating 10W Opening gap 50 - 60mm.

SOUNDER 12V

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

High power 130 db Police Siren Sound Suitable for Indoor and Outdoor application Tamper Loop Two sound speed options available white ABS Housing.

	Intrusion alarm Kit Includes		
SI	Product	Description	Quantity
1	Intrusion Control Panel-Wired	12 Zone Control Panel with Onboard Key Pad	1
2	PIR Motion Sensor	PIR Motion Sensor with Intelligent Pet Immunity	3
3	Dual Technology Magnetic Contact	Microcontroller based Dual Technology Magnetic Contact	2
4	Shutter Contact	Metal Shutter Contact	2
5	Sounder	High power 130 db, Police Siren Sound	1

Please Note: Product Specification and Model can be Changed without any Prior Notice



