

DEN-INTRUSION-KIT-04

For Large Group of Villas or Estate House

Intrusion Alarm Kit



Micro-controller based 24 zones control panel, Can expand up to 40 wired zones with expansion modules, Can connect up to 14 wireless sensors and key fobs by adding wireless receiver, Automatic arming and disarming, 1 admin user and 3 defined sub users, Inbuilt 2 Voice Message 20 number GSM dialer with multiple alarm and status SMS, Alarm Information communicated over GSM with alarm type, zone no, time and date Status SMS in case of system arm, disarm, code change, power on, power off & low battery, Android app to operate and program panel and receive alarm and status messages from panel, Sturdy sheet metal enclosure with advance technology tamper detection.

FEATURES:

Micro-controller based 24 zones control panel
Can expand up to 40 wired zones with expansion modules
Can connect up to 14 wireless sensors and key fobs by adding wireless receiver
Automatic arming and disarming, 1 admin user and 3 defined sub users
Inbuilt 2 Voice Message 20 number GSM dialer with multiple alarm and status SMS.



QUAD P.I.R. MOTION SENSOR

Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity. Detection Range 12m, Multi Angle wall bracket. ABS Housing.

TECHNICAL SPECIFICATION:

Detection method Passive infrared
Coverage 12m x 12m(40ft x 40ft) 85°wide
Detection zones 78 zones
Mounting height 1.5 to 2.4m (5 to 8ft)
LED alarm indicator Switchable ON/OFF
Alarm period Approx. 2.5 sec
Alarm output N.C., 24VDC 0.2A max.
Tamper switch N.C., Open when cover is removed.
Tamper output 24VDC 0.1A max.
PIR sensitivity/range Switchable LOW/MID/HI
Warm up period Approx. 30 sec
Power input 9.5 to 16VDC
Current consumption 8mA (normal), 11mA (max.) at 12VDC
Dimensions H93.4mm x W61.4mm x D46.0mm
Weight Approx. 70 g (with bracket: 90 g)
Operating temperature -20°C to +50°C (-4°F to +122°F)
Environmental humidity 95% max.
RF interference No alarm 10V/m

FEATURES:

Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity.
Detection Range 12m
Multi Angle wall bracket.
ABS Housing.



DUAL TECH MAGNETIC CONTACT

Microcontroller based Dual Technology Magnetic Contact with inbuilt Digital Multi Function Detector. Magnetic Contact Opening Gap 12-15mm. Inbuilt Digital Multi Function Detector. Detects vibration, breaking off glass, cutting off aluminium frames or grills.

Features:

Microcontroller based Dual Technology Magnetic Contact with inbuilt Digital Multi Function Detector. Magnetic Contact Opening Gap 12-15mm. Inbuilt Digital Multi Function Detector. Detects vibration
Breaking of glass
Cutting off aluminium frames or grills.



METAL SHUTTER CONTACT

Metal housing, material aluminium alloy, 2 wire , contact rating 10W, Opening gap 50 – 60mm.

Features:

Metal housing
Material aluminium alloy
2 wire
Contact rating 10W
Opening gap 50 – 60mm.



SOUNDER 12V

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

High power 130 db
Police Siren Sound
Suitable for Indoor and Outdoor application
Tamper Loop
Two sound speed options available
white ABS Housing.



BEAM DETECTOR 40 Mtr

Beam Detector with dual beam, 40 meter detection range, High grade spherical lens, Automatic Gain Control, Adjustable beam interruption period, IP 65, Lightning protection, Easy angle alignment.

Features:

Beam Detector with dual beam
40 meter detection range
High grade spherical lens
Automatic Gain Control
Adjustable beam interruption period

TECHNICAL SPECIFICATION:

DEN-INTRUSION-KIT-04



Detection Range : 40 Meter
Arrival Distance : 400 Meter
Technology : IR interruption detection time frame selectable
50msec/100msec/250msec/500msec
Operating Voltage : 11V DC to 28V DC
Rating Current : 38 mAmp
Alarm Contact : Normally Connected 28V DC , 0.2Amp
Beam Blocking Stability : 99%
Operating Temperature : 60 degrees Max.
Environmental Humidity : 95%
Alignment Angle : 90 degrees H , 5 degrees V



TECHNICAL SPECIFICATION:

Power supply, V DC : 9 to 17 V
Current consumption, max : 22 mA
IP rating : Ip30
Operating temperature : -20° to +45°C
Dimensions : 65x65x30 mm
Detection range : At minimum controlled area of 0.1 m2: 6 m
At minimum controlled area of 1.0 m2: 9 m

ACOUSTIC GLASS BREAK DETECTOR

Intelligent acoustic-based detection of breaking glass. Securico's Acoustic glass break detector helps in detecting the intrusion attempts into an area by breaking a window or glass.

Detecting destruction of the following types of glasses: common, quenched, patterned, armored, multilayer and protected with polymer tape (laminated), glass hollow blocks, as well as standard double- and triple-chamber windows, adjustable sensitivity.

FEATURES OF ACOUSTIC GLASS BREAK DETECTOR :

Intelligent acoustic-based detection of breaking glass.
Detecting destruction of the following types of glasses: common, quenched, patterned, armored, multilayer, and protected with polymer tape (laminated)
Detection range: 6-9m
Installation height: 2m
Alarm Message Duration: Not less than 2 sec
Generates Alarm message by alarm loop contact opening



DIGITAL MULTI FUNCTION DETECTOR

Microcontroller based digital MFD specially designed for ATM application. Detects intrusion attempts on an ATM based on 4 logics, advanced sensing algorithms. Sleek ABS housing with 3 LED indicators. *NEW sleeker design with advanced digital technology*

Features:

Microcontroller based digital MFD specially designed for ATM application.
Detects intrusion attempts on an ATM based on 4 logics, Advanced sensing algorithms.
Sleek ABS housing with 3 LED indicators.



SMART SENSOR

DENLOB's smart sensor is a stand-alone external PIR motion sensor with sensitivity, time, Lux, retrigger & bypass controls. Suitable for indoor and outdoor installation. Can switch up to 1000W electrical load. Security Device, Welcome Light, and Energy Saving Device.

Smart sensors turn on lights, fans, air conditioners, or any other electric device whenever any motion is detected in their coverage area and automatically turns them off when there is no motion.



Foot Panic Switch

Micro switch technology, foot pedal push, automatic reset, ABS body, metal base.

Features:

- Micro switch technology
- Foot pedal push
- Automatic reset
- ABS body
- Metal base.

Technical Specification:

- Contact O/P : Normally Closed/ Normally Open
- Housing : ABS
- Colour : Grey
- Rated Current : 12V to 28VDC
- Dimensions : (L) 83mm x (W)80mmx (H)30mm



STAND ALONE SMART SWITCH

DENLOB's smart switch is a stand-alone ceiling PIR motion sensor with sensitivity, time, lux, retrigger & bypass controls. Energy Saving Device, Automatic Switch, and Security Device. Can switch up to 400W electrical load.

Intrusion alarm Kit Includes			
SI	Product	Description	Quantity
1	Intrusion Control Panel-Wired	Micro-controller based 24 zones control panel, Can expand up to 40 wired zones with expansion	1
2	PIR Motion Sensor	PIR Motion Sensor with Intelligent Pet Immunity	6
3	Dual Technology Magnetic Contact	Microcontroller based Dual Technology Magnetic Contac	4
4	Shutter Contact	METAL SHUTTER CONTACT	1
5	Sounder	High power 130 db, Police Siren Sound	2
6	Beam Detector 40Mtr	BEAM DETECTOR 40 Mtr	1
7	Glass break Detector	Glass Break Detector	5
8	Stand Alone Lock Sensor	Stand Alone Lock Sensor	1
9	Stand Alone Energy Saving	Stand Alone Energy Saving Sensor	1
10	Panic Button	Foot Panic Button	1
11	Standalone Smart Lighting	Smart Switch for Lighting control	1

Please Note: Product Specification and Model can be Changed without any Prior Notice