DEN-VILLA-LITE



DEN-VILLA-LITE

This VILLA Lite is Suitable for Independent house with 3+BHK VILLA

Intrusion Alarm Kit



12 Zone Control Panel with Onboard Key Pad and Automatic Arming & Disarming, 10 programmable zones, can Connect Separate Remote Key Pads, Inbuilt Power Supply.

Feature:

12 Zone Control Panel with Onboard Key Pad. Automatic Arming & Disarming. 10 programmable zones.

Can Connect Separate Remote Key Pads.

Inbuilt Power Supply.

TECHNICAL SPECIFICATION:

ELECTRICAL

Quiescent current: 75ma typical with all LED's and internal

buzzer on

Maximum sounder current output: 1A Maximum Strobe light current output: 1A

Sounder and strobe saturation Voltage: <1V at 1A

Remote keypads: five (max)

Non volatile Memory: Programming and Log

Zone response time: <500mS

Zone Loop Resistance: <5kohm for Normally Closed

ENVIRONMENTAL

Operating Temperature: 0C to 45C Storage Temperature: -20C to 60C Maximum humidity: 95% non -condensing

Environment: residential / commercial / light Indus trial

POWER SUPPLY

Mains supply Voltage: 220+10% -15% 50Hz

Total current Output: 800MA at 220V AC (Fuse JA 20mm On

Main Card) Regulation: <9% Ripple: <200mv RMS Battery VOLTAGE: 12V DC Battery type: SMF Rechargeable

Battery Recharge voltage: 13.8V +/-0.2V DC

Fuse: 250ma 20mm AC Mains on Power Supply Card

Dimensions: 236 mm x 226mm x 80mm

Max Battery Dimensions: 150mm x 110mm x 64 mm



FEATURES:

- Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity.
- Detection Range 12m
- Multi Angle wall bracket.
- ABS Housing.

QUAD P.I.R. MOTION SENSOR

Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity. Detection Range 12m, Multi Angle wall bracket. ABS Housing.

TECHNICAL SPECIFICATION:

Detection method Passive infrared

Coverage 12m x 12m(40ft x 40ft) 85°wide

Detection zones 78 zones

Mounting height 1.5 to 2.4m (5 to 8ft)

LED alarm indicator Switchable ON/OFF

Alarm period Approx. 2.5 sec

Alarm output N.C., 24VDC 0.2A max.

Tamper switch N.C., Open when cover is removed.

Tamper output 24VDC 0.1A max.

PIR sensitivity/range Switchable LOW/MID/HI

Warm up period Approx. 30 sec Power input 9.5 to 16VDC

Current consumption 8mA (normal), 11mA (max.) at 12VDC

Dimensions H93.4mm x W61.4mm x D46.0mm

Weight Approx. 70 g (with bracket: 90 g)

Operating temperature -20°C to +50°C (-4°F to +122°F)

Environmental humidity 95% max. RF interference No alarm 10V/m

Page 1 of 3 Customer care: +91-7676209993

DEN-VILLA-LITE





2wire MAGNETIC CONTACT

Opening Gap 12-15mm, with mounting holes in collar for ease of installation. ABS Housing. Colour options – white and black

Features:

Opening Gap 12-15mm

With mounting holes in collar for ease of installation. ABS Housing.

Colour options - white and black.



GAS Leak Sensor

Gas leak detector to detect leakage of liquid petroleum gas and compressed natural gas.

Features:

Gas leak detector to detect leakage of liquid petroleum gas and compressed natural gas.



SOUNDER 12V

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

High power 130 db Police Siren Sound

Suitable for Indoor and Outdoor application

Tamper Loop

Two sound speed options available white ABS Housing.



ACOUSTIC GLASS BREAK DETECTOR

Intelligent acoustic-based detection of breaking glass. DENLOB's Acoustic glass break detector helps in detecting the intrusion attempts into an area by breaking a window or glass.

Detecting destruction of the following types of glasses: common, quenched, patterned, armored, multilayer and protected with polymer tape (laminated), glass hollow blocks, as well as standard double- and triple-chamber windows, adjustable

Page 2 of 3 Customer care: +91-7676209993

DEN-VILLA-LITE





VIDEO DOOR PHONE - ANALOGUE

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

High power 130 db
Police Siren Sound
Suitable for Indoor and Outdoor application
Tamper Loop
Two sound speed options available
white ABS Housing.

	Intrusion alarm & Video Door Phone Kit Includes		
SI	Product	Description	Quantity
1	Intrusion Control Panel-Wired	12 Zone Control Panel with Onboard Key Pad	1
2	PIR Motion Sensor	PIR Motion Sensor with Intelligent Pet Immunity	2
3	Siren	High power 130 db, Police Siren Sound	1
4	GAS Leak Sensor	Gas Leak Detectors	1
5	Glass Break Sensor	Glass Break Detector	2
6	Magnetic Contact	MAGNETIC CONTACT 2 WIRE with Collar	3
7	Lock Sensor- Standalone	Stand Alone Lock Sensor	2
8	Video Door Phone	7" TFT screen Analogue Video Door Phone	1

Please Note: Product Specification and Model can be Changed without any Prior Notice

Page 3 of 3 Customer care: +91-7676209993