

DEN-VILLA-PRE

This VILLA Premium is Suitable for Independent house with 5+BHK VILLA

Intrusion Alarm Kit



SECURITY & AUTOMATION IoT HUB

Micro-controller based 16 zones Security & Automation IOT Hub, 1 admin user, 1 engineering user and 18 system users, Fully feature loaded, Inbuilt TCP/IP communicator for fast, accurate and detailed monitoring & control, Inbuilt SMPS, Sturdy sheet metal enclosure with advance technology tamper detection. Optional Remote Keypad (not included).

Feature:

Micro-controller based 16 zones Security & Automation IOT Hub
 1 admin user
 1 engineering user and 18 system users
 Inbuilt TCP/IP communicator for fast, accurate and detailed monitoring & control



REMOTE KEY PAD FOR SECURITY & AUTOMATION IoT HUB

Remote key pad for IoT hub (16x2 LCD display).



QUAD P.I.R. MOTION SENSOR

Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity. Detection Range 12m, Multi Angle wall bracket. ABS Housing.

FEATURES:

- Digital Quad Technology PIR Motion Sensor with Intelligent Pet Immunity.
- Detection Range 12m
- Multi Angle wall bracket.
- ABS Housing.

TECHNICAL SPECIFICATION:

Detection method Passive infrared
 Coverage 12m x 12m(40ft x 40ft) 85°wide
 Detection zones 78 zones
 Mounting height 1.5 to 2.4m (5 to 8ft)
 LED alarm indicator Switchable ON/OFF
 Alarm period Approx. 2.5 sec
 Alarm output N.C., 24VDC 0.2A max.
 Tamper switch N.C., Open when cover is removed.
 Tamper output 24VDC 0.1A max.
 PIR sensitivity/range Switchable LOW/MID/HI
 Warm up period Approx. 30 sec
 Power input 9.5 to 16VDC
 Current consumption 8mA (normal), 11mA (max.) at 12VDC
 Dimensions H93.4mm x W61.4mm x D46.0mm
 Weight Approx. 70 g (with bracket: 90 g)
 Operating temperature -20°C to +50°C (-4°F to +122°F)
 Environmental humidity 95% max.
 RF interference No alarm 10V/m



2wire MAGNETIC CONTACT

Opening Gap 12-15mm, with mounting holes in collar for ease of installation. ABS Housing. Colour options – white and black

Features:

Opening Gap 12-15mm
With mounting holes in collar for ease of installation.
ABS Housing.
Colour options – white and black.



GAS Leak Sensor

Gas leak detector to detect leakage of liquid petroleum gas and compressed natural gas.

Features:

Gas leak detector to detect leakage of liquid petroleum gas and compressed natural gas.



SOUNDER 12V

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

High power 130 db
Police Siren Sound
Suitable for Indoor and Outdoor application
Tamper Loop
Two sound speed options available
white ABS Housing.



ACOUSTIC GLASS BREAK DETECTOR

Intelligent acoustic-based detection of breaking glass. DENLOB's Acoustic glass break detector helps in detecting the intrusion attempts into an area by breaking a window or glass.

Detecting destruction of the following types of glasses: common, quenched, patterned, armored, multilayer and protected with polymer tape (laminated), glass hollow blocks, as well as standard double- and triple-chamber windows, adjustable sensitivity.



THERMAL SENSOR

Micro controller based, Detects rate of rise in temperature
 Detects change in ambient temperature, Rate of rise detection logic and fixed temperature logic, Power LED and Alarm LED, compact design in sheet metal housing.

FEATURES:

Micro controller based.
 Detects rate of rise in temperature.
 Detects change in ambient temperature.
 Rate of rise detection logic and fixed temperature logic.
 Power LED and Alarm LED.
 Compact design in sheet metal housing.



BEAM DETECTOR 40 Mtr

Beam Detector with dual beam, 40 meter detection range, High grade spherical lens, Automatic Gain Control, Adjustable beam interruption period, IP 65, Lightning protection, Easy angle alignment.

Features:

Beam Detector with dual beam
 40 meter detection range
 High grade spherical lens
 Automatic Gain Control
 Adjustable beam interruption period

TECHNICAL SPECIFICATION:

Detection Range : 40 Meter
 Arrival Distance : 400 Meter
 Technology : IR interruption detection time frame selectable
 50msec/100msec/250msec/500msec
 Operating Voltage : 11V DC to 28V DC
 Rating Current : 38 mAmp
 Alarm Contact : Normally Connected 28V DC , 0.2Amp
 Beam Blocking Stability : 99%
 Operating Temperature : 60 degrees Max.
 Environmental Humidity : 95%
 Alignment Angle : 90 degrees H , 5 degrees V

DIGITAL MULTI FUNCTION DETECTOR



Microcontroller based digital MFD specially designed for ATM application. Detects intrusion attempts on an ATM based on 4 logics, advanced sensing algorithms. Sleek ABS housing with 3 LED indicators. *NEW sleeker design with advanced digital technology*

Features:

Microcontroller based digital MFD specially designed for ATM application.
 Detects intrusion attempts on an ATM based on 4 logics,
 Advanced sensing algorithms.
 Sleek ABS housing with 3 LED indicators.



VIDEO DOOR PHONE - ANALOGUE

High power 130 db, Police Siren Sound, Suitable for Indoor and Outdoor application.. Tamper Loop. Two sound speed options available. White ABS Housing.

Features:

High power 130 db
Police Siren Sound
Suitable for Indoor and Outdoor application
Tamper Loop
Two sound speed options available
white ABS Housing.

Intrusion alarm & Video Door Phone Kit Includes

SI	Product	Description	Quantity
1	Intrusion Control Panel-Wired	SECURITY & AUTOMATION IoT HUB	1
2	Remote Keypad	REMOTE KEY PAD FOR GALAXY 4816 IP / IOT	1
3	PIR Motion Sensor	PIR Motion Sensor with Intelligent Pet Immunity	3
4	Siren	High power 130 db, Police Siren Sound	1
5	Magnetic Contact	MAGNETIC CONTACT 2 WIRE with Collar	5
6	Thermal Sensor	THERMAL SENSOR	1
7	GAS Leak Sensor	Gas Leak Detectors	1
8	Beam Detector	BEAM DETECTOR 40 Mtr	1
9	Video Door Phone	Glass Break Detector	3
10	Lock Sensor- Standalone	Stand Alone Lock Sensor	1
11	Video Door Phone	7" TFT screen Analogue Video Door Phone	1
12	Additional Monitor	ADDITIONAL MONITOR FOR HEXA VDP	1

Please Note: Product Specification and Model can be Changed without any Prior Notice