





14"PC Ceiling Light Flush Mount with LED 16W/24W

A




B



Specification

Driver on Board LED light Engines

| Model Number | Photo | Size | Watts/CCT |
|--------------|--|-----------------|-----------|
| GL-R170-1630 |  | 170mm 6.7 in | 16W/3000K |
| GL-R170-1650 | | | 16W/3000K |
| GL-R170-2430 | | | 24W/3000K |
| GL-R170-2450 | | | 24W/3000K |

120V input, 50/60Hz, PF>0.9, Damp Location

Color Temperature: 3000K or 5000K, optional

CRI 80, 90 lm/W, Triac dimming of 100%-10%

Ambient temperature: -20°C to 45°C

3 years limited warranty

| Order Code | Size(mm) | CCT | Volt/Watts | Lumens |
|---------------|--------------|-------|------------|--------|
| GLCLS24WC-14A | ø350 x H:95 | 5000K | 120AC/24W | 1900 |
| GLCLS24WW-14A | ø350 x H:95 | 3000K | 120AC/24W | 1900 |
| GLCLS24WC-14B | ø350 x H:120 | 5000K | 120AC/24W | 1900 |
| GLCLS24WW-14B | ø350 x H:120 | 3000K | 120AC/24W | 1900 |
| GLCLS16WC-14A | ø350 x H:95 | 5000K | 120AC/16W | 1250 |
| GLCLS16WW-14A | ø350 x H:95 | 3000K | 120AC/16W | 1250 |
| GLCLS16WC-14B | ø350 x H:120 | 5000K | 120AC/16W | 1250 |
| GLCLS16WW-14B | ø350 x H:120 | 3000K | 120AC/16W | 1250 |