# Anchorage 2335

White <sup>†</sup> <b>2664</b>	Drift	Pearl	Shell	Dune	North Star	Dew	Foam	Fog	Overcast
	<b>8570</b>	<b>8573</b>	<b>8572</b>	<b>8583</b>	<b>8578</b>	<b>8579</b>	<b>8585</b>	<b>8586</b>	<b>8575</b>
Vanilla	Birch	Angora	Goose	Cumin	Shadow	Breeze	Slate	Wolf	Asteroid
<b>2130</b>	<b>2129</b>	<b>2035</b>	<b>2049</b>	<b>2050</b>	<b>6694</b>	<b>8582</b>	<b>2017</b>	<b>2027</b>	<b>2053</b>
Lemon	Sunshine	Straw	Goldenrod	Pumpkin	Eucalyptus	Green Apple	Willow	Fern	Pine Needle
<b>2839</b>	<b>2082</b>	<b>2034</b>	<b>2090</b>	<b>2021</b>	<b>2047</b>	<b>2087</b>	<b>2028</b>	<b>2840</b>	<b>2022</b>
Geranium	Poppy	Red Delicious	Mulberry	Orchid	Quarry Blue	Bay	Waterfall	Turquoise	Deep Water
<b>2084</b>	<b>2091</b>	<b>2014</b>	<b>2044</b>	<b>2843</b>	<b>2026</b>	<b>8703</b>	<b>2691</b>	<b>2841</b>	<b>2051</b>
Fossil	Graphite	Coffee Bean	Aubergine	Onyx	Pool	Lapis	Thistle	Cobalt	Midnight
<b>2093</b>	<b>2079</b>	<b>2083</b>	<b>2036</b>	<b>2016</b>	<b>2842</b>	<b>2094</b>	<b>2085</b>	<b>2045</b>	<b>2025</b>

†Suitable for printing



# **Specifications**

Content	100% post-consumer recycled polyester					
Weight	15.2 ± 1.0 oz./lin. yd					
Width	66" min. useable					
Repeat	none					

## **Cleaning Code**

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

#### Miscellaneous

- · Application testing of this product is recommended.
- · Colors may vary between dye lots.

Proudly woven in North America supporting our local communities.

# **Sustainability**

100% recycled and recyclable



Renowned for its exceptional performance and style, Guilford of Maine has set industry standards in acoustics and panel fabrics for many decades. We present the Guilford of Maine Collection - a selection of timeless fabrics.

#### **Performance**



Grade 4 min. at 40 hours Colorfastness to light (AATCC 16.3 Option 3)





Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet



Breaking Strength (ASTM D5034)
275 lbf min. warp and fill



Flammability

ASTM E84 Class I or A

### **Acoustical Performance**

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

#### **Acoustic Transparency:**

85%

For more detailed results, please consult our website.



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

Certification Marks owned by the Association for Contract Textiles, Inc



