



ADVANCED TECHNOLOGY IN LUBRICATION SINCE 1933

SWEPCO
702

Synthetic Universal AW Compressor Oil And Ashless Hydraulic Oil



**Exceptional Oil Life
Up to 8,000 Hours**

SWEPCO 702 Synthetic Universal AW Compressor Oil delivers exceptional wear control in the most demanding compressor applications.

SWEPCO's **Syntheon™** synthetic base stock blends and proprietary **LUBIUM® II** oxidation and corrosion resistant chemistry lengthen lubricant life, insure compressor cleanliness, reduce wear, improve compressor efficiencies, reduce energy consumption & boost productivity. Formulated for rotary, reciprocal & centrifugal compressors. When you want the best, choose SWEPCO 702.




KEY BENEFITS

- Dependable, long service life in rotary, reciprocating & centrifugal compressor applications
- Reliable service life up to 8,000 hours or more
- Truly superior anti-wear performance
- **Syntheon™** synthetic base stock blends insure exceptional high temperature performance
- Advanced **LUBIUM® II** anti-oxidant chemistry prevents carbon, varnish & other performance-robbing deposits
- Unexcelled protection from rust & corrosion
- Energy efficient, improves compressor efficiency
- Rated for discharge temperatures as high as 200°C
- Fluid down to -40°F (-40°C) for cold weather applications
- UV sensitive for fast leak detection
- Can be used in hydraulic systems requiring ashless AW protection

Get more work out of your compressors with SWEPCO 702 . . .



Rotary Screw



Rotary Vane



Reciprocating



Centrifugal

Maximize your productivity with hard working SWEPCO 702 Synthetic Universal AW Compressor Oil.

Feature	Benefit
Syntheon™ Base Stock Blends	<ul style="list-style-type: none"> • Gives you a more uniform viscosity over a wide temperature range • Improves high temperature oxidation and thermal stability • Better low temperature flow characteristics help reduce start-up wear • Extends service life
LUBIUM® II Anti-Oxidant	<ul style="list-style-type: none"> • Improves resistance to high temperature degradation • Helps prevent varnish and carbon deposits that result from oxidation
Anti-Wear Additive	<ul style="list-style-type: none"> • Protects surfaces from scuffing wear
Rust & Corrosion Inhibitor	<ul style="list-style-type: none"> • Builds a chemical bond with the surface to keep moisture and acids from penetrating and attacking the surfaces. Rust inhibitor protects metal surfaces and seals from moisture. Particularly effective during periods of shutdown, where cooling may cause condensation
Anti-Foam Additive	<ul style="list-style-type: none"> • Lowers oil operating temperatures up to 25 degrees F. or more by dispersing foam and releasing trapped heat
Pour Point Depressant Additive	<ul style="list-style-type: none"> • Gives oil better low temperature flow characteristics • Helps to reduce low temperature start-up wear
Energy Savings	<ul style="list-style-type: none"> • Provides thin friction reducing film on vital metal parts to reduce electrical consumption. Many customers have achieved amperage reductions as much as 13% • Documented electrical savings through SWEPCO's ESP program
Long Service Life	<ul style="list-style-type: none"> • Up to 8,000 hours and longer; reduces consumption; reduces waste oil disposal costs
LabTecSM Fluid Analysis Program	<ul style="list-style-type: none"> • Can maximize equipment life, life of the lubricant and pinpoint impending problems • Reduces waste
Bottom Line	Increased profits through... <ul style="list-style-type: none"> • Extended equipment life • Extended oil life • Reduced electrical utility costs • Reduced waste oil disposal • Reduced costly scheduled and unscheduled downtime • Reduced labor costs

Typical Physical Properties

ISO Viscosity Grade, ASTM 2422.....	32.....	46.....	68.....	100.....
SAE Grade.....	10.....	15.....	20.....	30.....
Density, @60°F, lb/gal, ASTM D1298.....	7.12.....	7.14.....	7.22.....	7.22.....
Specific Gravity @ 60 °F, ASTM 1298.....	0.85.....	0.86.....	0.87.....	0.87.....
Viscosity, ASTM D445				
cSt @ 40 °C.....	33.....	48.....	67.....	94.....
cSt @ 100 °C.....	5.67.....	7.26.....	10.90.....	13.12.....
Viscosity Index, ASTM D2270.....	111.....	110.....	153.....	139.....
Pour Point °F, ASTM D97, Max (°C).....	-40 (-40).....	-38 (-39).....	-37 (-38).....	-35 (-37).....
Flash Point °F, ASTM D92, Min (°C).....	400 (204).....	417 (214).....	420 (215).....	422 (217).....
Fire Point °F, ASTM D92, Min (°C).....	475 (246).....	500 (260).....	510 (265).....	515 (268).....
Color.....	reddish.....	reddish.....	reddish.....	reddish.....

Typical Performance Properties

Copper Strip Corrosion, ASTM D130, Color.....	1a
Rust, ASTM D665 A & B	
Distilled Water.....	pass
Synthetic Sea Water.....	pass
Acid Number, ASTM D974.....	0.13
Foam, ASTM D892, Seq I/II/III.....	0-0/0-0/0-0
Demulsibility, ASTM D1401	
oil/water/cuff (minutes).....	40/40/0 (10)
Oxidation, RPVOT minutes @150°C, ASTM D2272.....	1538
Oxidation, hrs to 2.0 TAN, ASTM D943.....	8,000+
Four Ball Wear, ASTM D4172	
1800 rpm, 1hr, 400N, scar diameter, mm.....	0.45
FZG Gear, DIN 51354 part 2, Damage Load Stage.....	>14
Conradson Carbon Residue, ASTM D189	
DIN 51352 part 1, Carbon residue after aging %.....	1.2
% evaporation Loss.....	2.3
DIN 51352 part 2, Carbon residue after aging %.....	2.5
% evaporation Loss.....	4.1
DIN 51356, DIN 51551, Residue after 80 vol% distillation	
Conradson carbon residue %.....	<0.1
Viscosity @ 40C before distillation.....	42.5
Viscosity @ 40C after distillation.....	74
Ratio of viscosity (5 max).....	1.74

Meets or Exceeds the Performance Requirements of These Specifications:

DIN 51506 (VBL, VCL, VDL), DIN 51524 Part II
 ISO/DP 6521 (DAA, DAB, DAH, DAG)
 USDA/NSF H2 & CFIA n1 (in closed systems)
 Denison HF-O, US Steel 127



TRIBO-CHEM LLC
 ralph.spence@tribo-chem.com
 281-731-8037
 tribo-chem.com

Compatibility

Gases - Ammonia, Nitrogen, Hydrogen, Helium, Carbon Monoxide, Carbon Dioxide (dry), Ethylene, Methane, Propane, Butane, Propylene, Butylenes, Natural Gas, Butadiene, Furnace crack gas, Hydrogen Sulfide (dry), Synthetic Gas, Sulfur Dioxide. NOT recommended for breathing air or refrigeration gases.

Paints - Epoxy, Oil Resistant Alkyd, Acrylic Enamel

Seals & Plastics - Acetal (Delrin), ABS, Phenolic, Poly-amideimide, Polyamide (Nylon), Polyester, Polyetherimide (Nylon), Polyimide, Polyphenylene oxide, Polystyrene, Polysulfone, PTFE (Teflon), Terephthalate Elastomers; Fluoroelastomer (Viton), Nitrile (Buna N), Polyacrylate, TFE/P, Poly Urethane. NOT recommended for polycarbonate plastic that is not metal covered, PVC plastic and butyl, ethylene propylene or SBR rubber.

Changeovers: Although compatible with mineral oils, PAOs and some other synthetic oils, a thorough drain and cleaning is recommended before switching over to SWEPCO 702. This will help reduce initial contamination and insure optimum performance. NOT compatible with polyalkylene glycol or silicone oils.



A Product of SPX Technology™.

... the cutting edge performance SWEPCO
 Customers have come to expect.



Southwestern Petroleum Lubricants, LLC

Fort Worth, Tx - Phone: (817)332-2336 - Fax: (800)736-5823 - www.swepcolube.com