



TDS N 413

TRAVERTINO DELL'ARTIGIANO **CONCHIGLIE SALENTO – SALE & PEPE**

INTERIOR/EXTERIOR

Lime-based decorative paste coating.

NOTE:

This technical data sheet describes two new finishes achievable with TRAVERTINO DELL'ARTIGIANO and can therefore be considered an extension of technical data sheet no. 412 for this decorative plaster.

PRODUCT DESCRIPTION

TRAVERTINO DELL'ARTIGIANO is a ready-to-use decorative plaster based on lime, natural fillers and marble granules. It offers high breathability, excellent workability, and the ability to create textured, elegant, and long-lasting surfaces. TRAVERTINO DELL'ARTIGIANO allows for customized aesthetic effects thanks to its application versatility and the possibility of integrating natural materials such as those listed below:

TRAVERTINO DELL'ARTIGIANO CONCHIGLIE SALENTO

Decorative finish featuring the integration of selected natural seashells to be added to the plaster.

This technique gives the surface a highly textured and authentic appearance, evoking the coastal traditions of Salento. The shells emerge harmoniously, creating relief patterns and textures that enhance the uniqueness of the wall. Ideal for rustic, Mediterranean-style interiors or projects with a strong visual impact.

CONCHIGLIE SALENTO are supplied in pre-measured packages to be mixed into the plaster, proportioned as follows:

- 6 kg TRAVERTINO DELL'ARTIGIANO + 1 package of CONCHIGLIE SALENTO 0.850 kg
- 24 kg TRAVERTINO DELL'ARTIGIANO + 2 packages of CONCHIGLIE SALENTO 1.7 kg

TRAVERTINO DELL'ARTIGIANO SALE & PEPE

Decorative variant obtained by adding mineral granules to the plaster. The result is an elegant, contemporary finish characterized by a speckled "salt and pepper" effect. This solution is particularly suitable for modern, refined interiors where a balance between naturalness and design is desired.

SALE & PEPE are supplied in pre-measured packages to be mixed into the plaster, proportioned as follows:

- 6 kg TRAVERTINO DELL'ARTIGIANO + 1 package of SALE & PEPE 0.250 kg
- 24 kg TRAVERTINO DELL'ARTIGIANO + 1 package of SALE & PEPE 1 kg

1. SURFACE PREPARATION

- Ensure the substrate is properly prepared and suitable for painting, i.e.: dry plaster, removal of any loose plaster granules; for old walls, remove any poor-quality, chalky or flaking paint.
- For new plaster: apply 1 coat of SCIK PURAL ACRIL primer diluted with water at a ratio of 1:10.
- Dilute DECOR FONDO with approximately 5–10% water depending on the substrate.



- Apply 1 or 2 coats of DECOR FONDO with a roller, depending on the substrate.
- Allow to dry completely (6–12 h depending on temperature).

NOTE:

- For new plaster, before applying DECOR FONDO, apply 1 coat of SCIK PURAL ACRIL primer diluted with water at a ratio of 1:10.

2. APPLICATION METHODS

APPLICATION OF TRAVERTINO DELL'ARTIGIANO CONCHIGLIE SALENTO

- Color TRAVERTINO DELL'ARTIGIANO using the tinting system (see color chart).

IMPORTANT: The first coat of this finish requires the application of TRAVERTINO DELL'ARTIGIANO in the desired color but without shells, as described in technical data sheet no. 412 for TRAVERTINO DELL'ARTIGIANO.

- Apply one coat of colored TRAVERTINO DELL'ARTIGIANO using a stainless steel trowel, spreading a uniform layer over the previously prepared surface.
- Allow to dry completely (12–24 h depending on temperature).

PREPARATION OF TRAVERTINO DELL'ARTIGIANO CONCHIGLIE SALENTO

- Color TRAVERTINO DELL'ARTIGIANO using the same color as the first coat.
- Pour the corresponding quantity of CONCHIGLIE SALENTO into the colored TRAVERTINO DELL'ARTIGIANO.
- Mix thoroughly using a mechanical mixer at low speed until a homogeneous mixture is obtained.

NOTE:

It is recommended to prepare the mixture 12–24 hours before application; this will give the plaster a thicker consistency for better workability.

- Apply the coat of TRAVERTINO DELL'ARTIGIANO with CONCHIGLIE SALENTO using a stainless steel trowel, ensuring that the layer is applied following the thickness of the shells.
 - After 15–30 minutes depending on temperature, use the stainless steel trowel to begin smoothing the surface.
- Allow to dry completely (24 h depending on temperature).
 - After complete drying, sand the surface with 80-grit sandpaper to remove any imperfections and make the shells more visible.
 - Depending on the desired effect, continue sanding progressively with 120, 240, and 400-grit sandpaper until the desired level of sheen is achieved.
- Remove any dust created during sanding from the surface.



APPLICATION OF TRAVERTINO DELL'ARTIGIANO SALE & PEPE

- Color TRAVERTINO DELL'ARTIGIANO using the tinting system (see color chart).

IMPORTANT: The first coat of this finish requires the application of TRAVERTINO DELL'ARTIGIANO in the desired color but without mineral granules, as described in technical data sheet no. 412 for TRAVERTINO DELL'ARTIGIANO.

- Apply one coat of colored TRAVERTINO DELL'ARTIGIANO using a stainless steel trowel, spreading a uniform layer over the previously prepared surface.
- Allow to dry completely (12–24 h depending on temperature).

PREPARATION OF TRAVERTINO DELL'ARTIGIANO SALE & PEPE

- Color TRAVERTINO DELL'ARTIGIANO using the same color as the first coat.
- Pour the corresponding package of SALE & PEPE into the colored TRAVERTINO DELL'ARTIGIANO.
- Mix thoroughly using a mechanical mixer at low speed until a homogeneous, well-distributed mixture is obtained.

NOTE:

It is recommended to prepare the mixture 12–24 hours before application; this will give the plaster a thicker consistency for better workability.

- Apply the coat of TRAVERTINO DELL'ARTIGIANO with SALE & PEPE using a stainless steel trowel, ensuring an even layer is spread over the surface.
 - After 15–30 minutes depending on temperature, use the stainless steel trowel to smooth the surface.
 - Allow the first coat to dry completely (24 h depending on temperature).
 - After complete drying, sand the surface with 80-grit sandpaper to remove any imperfections and make the granules more visible.
 - Depending on the desired effect, continue sanding progressively with 120, 240, and 400-grit sandpaper until the desired level of sheen is achieved.
- Remove any dust created during sanding from the surface.

3. PROTECTIVE COATINGS FOR TRAVERTINO DELL'ARTIGIANO CONCHIGLIE SALENTO AND TRAVERTINO DELL'ARTIGIANO SALE & PEPE

For enhanced protection of *TRAVERTINO DELL'ARTIGIANO CONCHIGLIE SALENTO* and *TRAVERTINO DELL'ARTIGIANO SALE & PEPE*:

- Apply one coat of HYDRO FINISH SPECIAL PLUS with a roller and allow to dry completely (see relevant technical



data sheet).



- After 12–24 hours, for increased water repellency, apply the wax-based solution with a sponge and allow to dry completely (see relevant technical data sheet).

NOTE:

For exterior applications, after applying and allowing HYDRO FINISH SPECIAL PLUS to dry, it is recommended to replace the wax-based solution with SCUDO M protective coating (see relevant technical data sheet).



TECHNICAL DATA

Nature of the binder	Vinyl resin
Viscosity	N/A
Drying	12-24h depending on temperature.
Dilution	Ready to use
Yield	1st coat of TRAVERTINO DELL'ARTIGIANO : 1,2-1,5 Kg/mq depending on the substrate. 2nd coat of TRAVERTINO DELL'ARTIGIANO CONCHIGLIE SALENTO : 1,500 Kg/mq depending on the substrate. 2nd coat of TRAVERTINO DELL'ARTIGIANO SALE &PEPE: 1,2-1,5 Kg/mq depending on the substrate
Specific Weight	N.A
Colors Available	See colour chart
Applied Appearance	Travertine marble effect with shells or speckled effect
Appearance in Packaging	Paste
Package Storage	Max +30°C, Min +5°C
Stability	2 years (in unopened original packaging)
VOC	200 g/l
PH	11-12°C
Tools cleaning	Soap and water
Package	- TRAVERTINO DELL'ARTIGIANO CONCHIGLIE SALENTO: 6KG TRAVERTINO DELL'ARTIGIANO + 0,850KG package of CONCHIGLIE SALENTO 24KG TRAVERTINO DELL'ARTIGIANO + two 1,7KG CONCHIGLIE SALENTO - TRAVERTINO DELL'ARTIGIANO SALE & PEPE: 6KG TRAVERTINO DELL'ARTIGIANO 6 + 0,250KG SALE & PEPE 24KG TRAVERTINO DELL'ARTIGIANO + 1KG SALE & PEPE

CHARACTERISTICS

Characteristics	Breathable
Applicable on	Walls, wood
Usage	Interior/Exterior
Certified	Class A
Related products and tools	
Tools	ABILE LUX trowel
Related products	DECOR FONDO, HYDRO FINISH SPECIAL PLUS, SOLUZIONE CEROSA, SCUDO M



NOTE:

- N.1 Attention, the Specific Weight indicated may not coincide with the Net Weight of the package due to technical coloring reasons .
- N.2 The stability period is purely indicative, it refers to the minimum stability time of the product if stored in good conditions according to the instructions provided, in the original unopened containers and in suitable temperature conditions. If stored adequately the product can have greater stability than the minimum recommended period.
- N.3 Rivedil guarantees that the information in this sheet is provided to the best of its experience and of his technical and scientific knowledge, however, being elements such as atmospheric conditions, manpower, tools, quality of third party products and others, outside the direct control of Rivedil, this document does not constitute a guarantee, nor Rivedil authorize its agents and/or representatives to provide any type of guarantee
- N.4 The raw materials used are natural and may have small differences depending on the batches used. It is therefore recommended that each job be finished with materials from the same batch of manufacture. Where this is not possible, it is recommended that batches be mixed with each other.

This cancels and replaces any previous form.

