



TECHNICAL DATA SHEET N°407

COLORS OF ITALY

Decorative fibrous paste to be coated with wax

PRODUCT DESCRIPTION


COLORI D'ITALIA is a decorative fibrous paste for interiors and exteriors.

The product allows you to decorate rustic interior environments or external facades where you want to reproduce an antique effect.

Colori d'Italia has breathable, sound-absorbing and thermal characteristics.

INDICATIONS FOR USE

- Make sure the support is dry. In the case of plaster, make sure it has a curing time of at least 28 days, based on the temperature.
- Make sure that the support has been prepared well and that it is suitable for painting: dry plaster, removal of any plaster granules; in the case of old walls, make sure that there is no poor-quality or powdery paint, and remove it if necessary; remove flaking paint etc.
- Apply 1 coat of SCIK PURAL ACRIL insulation if necessary.
- Proceed with the application of one or two coats of DECOR FONDO with a brush or roller, diluted with water in the following percentages: approximately 5-10%.
- Apply Colori d'Italia with a stainless steel trowel, smoothing the entire surface with plenty of product, with irregular and rustic strokes.
- Before completely drying, blend the product with the TD Spatula.
- Leave to dry perfectly for approximately 12-24 hours depending on temperature.
- Apply the colored CI Wax with the ceiling, making rotary movements to blend the product.
- After about 15-20 minutes after applying the wax, go over with paper, blending and antiqued the wax.

TECHNICAL DATA	
Nature of the Binder	Acrylic resin
Viscosity	
Drying	2 hours at 20°C, 6-12 hours complete.
Dilution	Ready to use
Surrender	0.50-0.60m²/Lt
Specific weight	1,355Kg/Lt
Available colours	White
Applied Aspeus	Anco
Aspeo in packaging	Pasty
Storage	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in original unopened packaging)
VOC	10µGr/m³
TVOC	40µGr/m³
PH	11-12°C
Cleaning Arezzi	Water and soap
Packaging	4LT, 10LT, 15LT
CHARACTERISTICS	
Features:	Breathable, sound-absorbing, heat-insulating.
Applicable on:	Walls.
For:	Interior/Exterior.
Check:	
RELATED TOOLS AND PRODUCTS	
Arezzo:	ar, Spatola TD.
Related Product:	BACKGROUND DECOR.

NOTE

- N.1 Attention: the Specific Weight indicated may not coincide with the Net Weight of the package for technical coloring reasons
- N.2 The stability period is purely indicative, it refers to the minimum stability time of the product if stored in good condition conditions according to the instructions provided, in the original unopened containers and in suitable temperature conditions. If stored adequately the product life can be more than 2 years and can have stability of several years.
- N.3 Rivedil guarantees that the information in this sheet is provided to the best of its experience and its own technical and scientific knowledge, however, being elements such as atmospheric conditions, manpower, tools, quality of third party products and others, outside the direct control of Rivedil, this document does not constitute a guarantee, nor does Rivedil authorize the its agents and/or representatives to provide any type of guarantee based on the information contained in this document. Yes recommends always checking the actual suitability of the product for the individual specific case. This cancels and replaces any previous tab.