



TDS 403

**INTERIOR AND
EXTERIOR**

PRODUCT DESCRIPTION

STILE BAROCCO VENEXIAN

Venetian effect glossy decorative plaster

STILE BAROCCO VENEXIAN is a decorative plaster based on special binders and mineral fillers, ideal for reproducing the ancient Venetian process of glossy trowelled plaster. It is particularly suitable for classic environments, but due to its composition it helps to create effects with a more modern style.

INDICATIONS FOR USE

1. PREPARATION OF THE SUBSTRATE:

- Make sure that the substrate is adequately prepared and suitable for painting, i.e.: dry plaster, removal of any plaster granules; in the case of old walls, remove any poor-quality, floury or flaking paint.
- Dilute DECOR FONDO with water at approximately 5-10% depending on the substrate.
- Apply 1 or 2 coats of DECOR FONDO with a roller depending on the support.
- Wait for complete drying (6-12 hours depending on the temperature).
- Sand the substrate with 280 sandpaper.

NOTE: In case of new plaster, before proceeding with DECOR FONDO, apply 1 coat of SCIK PURAL ACRIL insulation diluted with water 1:10.

2. STILE BAROCCO VENEXIAN APPLICATION:

▪ TRADITIONAL APPLICATION:

- Apply a coat of STILE BAROCCO VENEXIAN in the desired color with a stainless steel trowel (see color chart), evenly distribute the product, smooth the surface completely.
- Wait for complete drying (6-12 hours depending on the temperature).
- Sand with 280 sandpaper to eliminate any imperfections.
- Evenly apply the second-third coat (wet on wet application) of STILE BAROCCO VENEXIAN and continue smoothing the surface with the trowel, exerting adequate pressure to obtain the desired polish.
- Wait for complete drying (12-24 hours depending on the temperature)

NOTE:

STILE BAROCCO VENEXIAN also lends itself to further more modern processes such as the "HAND APPLIED VENEXIAN MARBLE SALENTO" application.

To see the application we recommend viewing the application video on RIVEDIL social channels.

3. PROTECTIVES FOR STILE BAROCCO VENEXIAN:

For greater protection and washability of STILE BAROCCO VENEXIAN we recommend the application of HYDRO CERA D'ARTE NEUTRA or CERA D'ARTE (for application see relevant technical data sheets).

NOTE:

To obtain further mirror effect of STILE BAROCCO VENEXIAN, before applying the desired wax, polish the surface progressively using 3000 – 5000 – 6000 abrasive papers.



Then proceed with the application and polishing of HYDRO CERA D'ARTE NEUTRA or CERA D'ARTE based on the desired effect (For the application, see the relevant technical data sheets.) .
Finally proceed (as per the technical data sheet) with polishing using a clean fabric.



TECHNICAL DATA

NATURE OF THE BINDER	Vinyl
VISCOSITY	N/A
DRYING	2 hours to touch, 12-24 hours complete.
DILUTION	Ready to use
YIELD	1 kg per 1m ² finished (2 coats)
SPECIFIC WEIGHT	1 Kg/Lt
COLORS AVAILABLE	See color chart
APPLIED APPEARANCE	Polished Venetian plaster
PRODUCT NATURE	White pasty
PACKAGE STORAGE	Max Temp. +30°C, Min T. +5°C
STABILITY	2 years (in original unopened packaging)
VOC	200 g/l
PH	7-8°C
TOOLS CLEANING	Soap and Water
PACKAGE	1KG, 5KG, 20KG

Characteristics

FEATURES	Washable, Ecological
APPLICABLE ON	walls, wood
USAGE	Interiors, Exteriors.
CERTIFIED	A

Related products and tools

TOOLS	Stainless steel trowels ABILE LUX or TOTAL BLACK
RELATED PRODUCTS	DECOR FONDO, HYDROCERA D'ARTE, CERA D'ARTE.

NOTE

N.1 - Attention, the Specific Weight indicated may not coincide with the Net Weight of the package due to technical coloring reasons .

N.2 - The stability period is purely indicative, it refers to the minimum stability time of the product if stored in good conditions according to the instructions provided, in the original unopened containers and in suitable temperature conditions. If stored adequately the product can have greater stability than the minimum recommended period.

N.3 - Rivedil guarantees that the information in this sheet is provided to the best of its experience and of his technical and scientific knowledge, however, being elements such as atmospheric conditions, manpower, tools, quality of third party products and others, outside the direct control of Rivedil, this document does not constitute a guarantee, nor Rivedil authorize its agents and/or representatives to provide any type of guarantee

N.4 -The raw materials used are natural and may have small differences depending on the batches used. It is therefore recommended that each job be finished with materials from the same batch of manufacture. Where this is not possible, it is recommended that batches be mixed with each other.

This cancels and replaces any previous form.