

R12

1/2" x 5"

R13 (N&F)

1 1/2" Ø (1.66" O.D.) SCHED. 40
TOP & BOTT. RAILS (TYP.)

1 1/2" Ø (1.66" O.D.) SCHED. 80
POSTS @ 4'-0" MAX. TYP

1 1/2" x 3/16" B.B. @ 1 3/16" o.c.
w/ C.B. @ 4" o.c. WELDED
GALV. STL. GRATING (19-W-4)
ATTACH w/ SADDLE CLIPS, 4 PER
PANEL MIN.

EL. = 169'-9 1/2"

P2

3'-0"

3'-7" V.I.F.

L4x4x3/8 STRUT

P2

V.I.F.
G.C. TO PROVIDE
ACCESS

C6x8.2

MC12x10.6
STRINGER TYP.

1 1/2" x 3/16" B.B. @ 1 3/16" o.c.
w/ C.B. @ 4" o.c. WELDED
GALV. STL. GRATING
TREADS (19-W-4)

EL. = 166'-1"

PL. 3/4" x 4 1/2" x 4 1/2"
w/ (1)-3/4" Ø W.A.

L4x4x3/8 x 9' LG.
w/ (2)-3/4" Ø W.A.
w/ 3' EMBED.

ST @ 11" = 4'-7"

5R @ 6' = 3'-0"