

FLEXIBLE TUBULAR HEATER FOR HR /vtANIFOLDS



- **Available Dia 6.5/8.00 & 8.50mm**
- Standard length available 400mm upto 1750mm (tolerance+1.5%)
- Effortless forming for easy installation
- Maximum sheath contact (upto75%)
- Rapid heat transfer and distribution
- Minimum temp. Variance between heater

sheath & manifold

- Reduce energy costs
- Smaller bending radius (12mm)
- Groove dimension –
- For 6.5mm : 6.02(w) (+0.05)mm x 6.50(h)(+0.10)mm,
- For 8 mm : 7.80(w) (+0.05) mm x 8.00(h)(+0.10)mm.
- For 8.5 mm : 8.30(w) (+0.05)mm x 8.50(h)(+0.10) mm

FEATURES

1. Available in chrome nickel steel
 2. Sealed edges to prevent from moisture
 3. Superior grade magnesium oxide insulated
 4. Swaged from good electrical insulation & heat transfer
 5. Available in round dia starting from 5mm, 6mm, 6.5mm, 8mm, 8.5mm
1. Available in square size starting from 6 x 6mm, 8 x 8mm,
 2. Standard length: 250mm upto 2500mm.

LENGTH	WATTS
400	800
450	900
500	T000
550	1150
600	1250
650	1400
700	1500
750	1600
800	1750
850	1850
900	1950
950	2100
1000	2200
1050	2300
1100	2450
1150	2550
1200	2650
1250	2800
1300	2900
1350	3000
1400	3150
1450	3250
1500	3350
1550	3051
1600	3149
1650	3248
1700	3346
1750	3444