### JK 2007 - 2018 EZFREEDOM FLIP- TOP

EZ4 4 EZTRUCK" ASSEMBLY

## MANUAL

#1907 0160

# We have made INSTALLATION EZ!

Scan the QR Code below for Step-by-Step Video Installation #1907 0160



**SCAN ME** 



Scan QR CODE for all other Videos & PDF MANUALS



# **Customer Service**

Any question? WE ARE HERE TO HELP!

203-901-0055 / Call 203-591-9060 EMAIL US: SERVICE@EZTRUNK.NET

7 days a week 8:30 am EST

### WE CAN HELP YOU WITH YOUR INSTALL!

PO#:

### BEFORE BEGINNING, Watch the Latest Video Manual

#### **CALL WITH ANY QUESTIONS OR FOR MISSING PARTS**

NO	Illustration	Description	Part#	2Dr QTY. #1907 0160
1	small cut at side edge	Driver / Left Freedom Top Hinge	1907146D	1
2	small cut at side edge	Passenger / Freedom Top Right Hinge	1907146P	1
3		JK Lock Kit	190714601	2
4		Alignment Template	1907146-70	1
5	Rubber	Rubber Pads	25250301	6
6	Adhesion Promoter	Adhesion Promoter	20	8
7		Short Bolt for Hardtop	061802	4
8		Long Bolt for Freedom Top	063802	4
9		Lock Nut M6	10062	8+1 extra
10	0	Rubber Washer	06012	8+1 extra
11	0	Metal Washer	16012	8+1 extra
12		#10 & #13 Wrench	#10	1
13	- F	Star Wrench-T30	60030	1
14		Drill Bit	#6	1

#### **RECOMMENDED TOOLS**















#### WARNING

EZFreedom Flip Top Hinge is designed to be installed on a roof with a factory finish, the product has not been tested on after-market finishes. The product warranty is void if the EZFreedom Flip Top Hinge is installed on a roof with any modifications or changes to the finish.

Wash and dry roof prior to installation concentrating on the hinge location area.

Ambient temperature should be at least 70F for proper adhesion of the EZFreedom Flip Top Hinge.

Please allow the Freedom Top Hinge to cure 24 hours before use.

WARNING This product is intended to provide added "off-road" convenience and utility to your vehicle. This product is not intended to provide occupant containment or protection in the event of an accident or rollover. Further, "on road" use may involve increased risk of serious injury in the event of side-impact accidents. To reduce risk from these types of injuries: Always wear seat belt and shoulder harness for all vehicle occupants. Keep arms and body inside vehicle. Drive safely, read and understand all manufacturers warnings and product instructions before installation. Periodically check and adjust all latches and fasteners, Failure to do so could result in the doors not latching securely.