JL 2018 - PRESENT EZFREEDOM FLIP- TOP

EZ 4 Z EZTRUCK ASSEMBLY

MANUAL

#1918 0061

We have made INSTALLATION EZ!

Scan the QR Code below for Step-by-Step Video Installation #1918 0061



SCAN ME



Scan QR CODE for all other Videos & PDF MANUALS



Customer Service

Any question? WE ARE HERE TO HELP!

203-901-0055 / Call 203-591-9060 EMAIL US: SERVICE@EZTRUNK.NET

7 days a week 8:30 am EST

WE CAN HELP YOU WITH YOUR INSTALL!

PO#:

BEFORE BEGINNING, Watch the Latest Video Manual

Please read instructions fully before beginning assembly

NO	Illustration	Description	Part#	JL QTY. #1918 0061
1	small cut at side edge	Driver / Left Freedom Top Hinge	1918061D	1
2	small cut at side edge	Passenger / Freedom Top Right Hinge	1918061P	1
3		JL Lock Kit - Drive	191806101	1
4		JL Lock Kit - Passenger	191806102	1
8		Alignment Template	191806106-90	1
9	Rubber	Rubber Pads	25250301	6
10	Adhesion Promoter	Adhesion Promoter	20	8
11		Short Bolt for Hardtop	061802	10
12		Lock Nut M6	10062	10+1 extra
13	0	Rubber Washer	06012	10+1 extra
14	0	Metal Washer	16012	10+1 extra
15		#10 & #13 Wrench	#10	1
16		Star Wrench-T30	60030	1
17		Drill Bit	#6	1

RECOMMENDED TOOLS















WARNING

EZFreedom Flip Top Hinge is designed to be installed on a roof with a factory finish, the product has not been tested on after-market finishes. The product warranty is void if the EZFreedom Flip Top Hinge is installed on a roof with any modifications or changes to the finish.

Wash and dry roof prior to installation concentrating on the hinge location area.

Ambient temperature should be at least 70F for proper adhesion of the EZFreedom Flip Top Hinge.

Please allow the Freedom Top Hinge to cure 24 hours before use

WARNING This product is intended to provide added "off-road" convenience and utility to your vehicle. This product is not intended to provide occupant containment or protection in the event of an accident or rollover. Further, "on road" use may involve increased risk of serious injury in the event of side-impact accidents. To reduce risk from these types of injuries: Always wear seat belt and shoulder harness for all vehicle occupants. Keep arms and body inside vehicle. Drive safely, read and understand all manufacturers warnings and product instructions before installation. Periodically check and adjust all latches and fasteners, Failure to do so could result in the doors not latching securely.