

## 5m & 6m Low Disturbance Loosener With Rear Packer



[www.grangemachinery.co.uk](http://www.grangemachinery.co.uk)

**GRANGE**  
MACHINERY

## 5m & 6m Low Disturbance Loosener With Rear Packer



The 6 Metre Low Disturbance Loosener wings are hydraulic folding and can be adjusted into work and transport mode from the tractor cab. For field work, the wings unfold, interlocking into a rigid 6 metre machine and for road transport, the machine folds neatly behind the tractor and is secured with a locking bar.



- 5-6 metre working width
- Low disturbance loosening legs with a range of 300mm working depth
- Hydraulic front cutting discs for trash management and to provide minimal disturbance
- Option of Seeder mounting platform and bracketry available
- Choice of packer to suit soil type

The main frame is lifted and lowered into work on the tractor link arms. The front discs are hydraulically operated to provide a good range of cutting depth according to surface conditions and to aid trash flow easily adjusted with depth clips. The depth of machine is controlled via the rear packer with a simple pin system.

These machines are very popular with direct drilling customers who want to lift and loosen the soil structure without disturbing the surface and creating another pass prior to drilling.



The machine is built with low disturbance legs and points which provide a full width lift with minimal surface disturbance. The front cutting disc enhances the loosening element of the leg and eliminates the surface tension, thus reducing any opportunity of soil boiling in front of the leg, along with easing the flow of trash through the machine.

