

# TECHNICAL SPECIFICATIONS

## NOTABLE BENEFITS

### Site Preparation

None

### Mode of Transportation

1 Pick-up truck or hauling vehicle

### Wind Resistance

115 mph (185 km/h) without windwalls or  
77 mph (123 km/h) with windwalls

### Promotional Visibility

Rolling billboard or banners and posters

### Backdrop\*

Weatherproof - fire retardant vinyl or scrim

### Vertical and Horizontal Banner Supports\*

Installed at ground level

TRAILER		
Length	31' 9"	9.69 m
Width	8' 0"	2.43 m
Height	11' 2"	3.40 m
Dry Weight	9,460 lb	4,290 kg
Maximum Weight	15,000 lb	6,804 kg
STAGE FLOOR		
Length and Depth	24' x 20' 1"	7.32 x 6.1 m
Height	3' 6" to 4' 3"	1.07 x 1.30 m
Design Live Load	150 lb/ft²	732 kg/m²
Type of Surface	Plywood on aluminium	
ROOF		
Length and Depth	25' 1" x 23' 9"	7.64 x 7.23 m
Clearance (Inclined roof)	14' 6" to 13' 2"	4.43 to 4 m
Height (from ground)	19' 0" to 19' 9"	5.79 to 6.02 m
Type of Surface	Fiberglass moulded around aluminum structure	
Roof Lifting Capacity	3,800 lb	1,725 kg
Roof Load Bearing Capacity	2,400 lb	5,190 kg
2 Trusses - Downstage & Upstage (T2)	1,200 lb (each)	544 kg (each)
2 Trusses - Central Roof (T1)	1,500 lb (each)	680 kg (each)
2 Front Overhang Extensions*	350 lb at 33" each	159 kg at 0.84 m each
2 Side Overhang Rigging Beams	1500 lb (each) 750 lb at 75" each	680 kg (each) 340 kg at 1.89 m each

† Please refer to rigging plan.

\* Optional

Values indicated are nominal. Due to STAGELINE'S product improvement policy, technical specifications may change without notice.