

SAFETY DATA SHEET Active XLS

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Active XLS

Product number 212

Internal identification 212-8

UFI: 46K0-N00N-S00U-9GYH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent. - Traffic Film Remover

Uses advised against For professional use only. This product is not recommended for any industrial, professional or

consumer use other than the Identified uses above.

1.3. Details of the supplier of the safety data sheet

Supplier Autosmart International Ltd

Lynn Lane

Shenstone, nr Lichfield Staffordshire. WS14 0DH

England

www.autosmartinternational.com

Tel: +44 (0) 1543 481616 (09:00 - 17:00)

SHREQ@autosmart.co.uk

Contact person Mr. Russell Butler

Manufacturer Autosmart International Ltd

Lynn Lane,

Shenstone, nr Lichfield Staffordshire. WS14 0DH

England

www.autosmartinternational.com

Tel: +44 (0) 1543 481616 (09:00 - 17:00)

info@autosmartinternational.com

1.4. Emergency telephone number

Emergency telephone NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call

NCEC at +44 1865 407333 (24Hrs UK)

when calling please quote "AUTOSMART 29003-NCEC"

If you urgently need medical help or advice but it's not a life-threatening situation, call 111 free from any phone to speak to an NHS adviser. The 24-hour NHS 111 service can give you

healthcare advice or direct you to the local service that can help you best.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Met. Corr. 1 - H290

Health hazards Skin Corr. 1C - H314 Eye Dam. 1 - H318

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

UFI: 46K0-N00N-S00U-9GYH

Contains sodium hydroxide, Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Detergent labelling < 5% amphoteric surfactants, < 5% non-ionic surfactants, < 5% NTA (nitrilotriacetic acid) and

salts thereof

Supplementary precautionary

statements

P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention.

P390 Absorb spillage to prevent material damage.

P406 Store in a corrosion-resistant/... container with a resistant inner liner.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

trisodium nitrilotriacetate 3<5%

Classification

Acute Tox. 4 - H302 Eye Irrit. 2 - H319 Carc. 2 - H351

Active XLS

sodium hydroxide 1-2%

CAS number: 1310-73-2 EC number: 215-185-5

Substance with a Community workplace exposure limit.

Classification

Met. Corr. 1 - H290 Skin Corr. 1A - H314 Eye Dam. 1 - H318

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10

1<1.25%

EO)

Classification

Acute Tox. 4 - H302 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Chemical burns must be treated by a physician.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery

position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin contact It is important to remove the substance from the skin immediately. Take off immediately all

contaminated clothing. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention. Chemical burns must be treated by a physician.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is

suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or

wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

Active XLS

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Corrosive to the respiratory tract.

Symptoms following overexposure may include the following: Severe irritation of nose and

throat.

Ingestion May cause chemical burns in mouth, oesophagus and stomach. Symptoms following

overexposure may include the following: Severe stomach pain. Nausea, vomiting.

Skin contact Causes severe burns. Symptoms following overexposure may include the following: Pain or

irritation. Redness. Blistering may occur.

Eye contact Causes serious eye damage. Symptoms following overexposure may include the following:

Pain. Profuse watering of the eyes. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Severe corrosive hazard. Water used for fire extinguishing, which has been in contact with the

product, may be corrosive.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Very

toxic or corrosive gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic

environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Regular protection may not be safe. Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's

clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of dust and vapours. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes. Avoid contact with contaminated tools and objects.

6.2. Environmental precautions

Environmental precautions

The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. This product is corrosive. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Neutralise with acid. Caution. May generate heat. Following dilution and neutralisation, discharge to the sewer with plenty of water may be permitted. The requirements of the local water authority must be complied with if contaminated water is flushed directly to the sewer. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. This product is corrosive. Immediate first aid is imperative. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in accordance with local regulations. Store away from the following materials: Acids.

Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Store in corrosive resistant container with a resistant inner liner. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not

i the event of spillage. The storage area hoof should

absorbent.

Storage class Corrosive storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

sodium hydroxide

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit.

trisodium nitrilotriacetate (CAS: 5064-31-3)

Ingredient comments No exposure limits known for ingredient(s).

DNEL Industry - Inhalation; Short term : 5.25 mg/m³

Industry - Inhalation; Long term : 3.5 mg/m³
Consumer - Inhalation; Short term : 1.75 mg/m³
Consumer - Inhalation; Long term : 0.5 mg/kg/day

PNEC - Fresh water; 0.93 mg/l

- marine water; 0.093 mg/l

- STP; 540 mg/l

Sediment; 3.64 mg/kgSoil; 0.182 mg/kg

sodium hydroxide (CAS: 1310-73-2)

DNEL Consumer - Inhalation; Short term : 1 mg/m³

Industry - Inhalation; Short term : 1 mg/m³ Industry - Inhalation; Long term : 1 mg/m³

8.2. Exposure controls

Protective equipment









Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment that provides appropriate eye and face protection should be worn. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: > 0.2 mm The selected gloves should have a breakthrough time of at least 0.5 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges suitable for intended use should be used. Full face mask respirators with replaceable filter cartridges suitable for intended use should be used. Half mask and quarter mask respirators with replaceable filter cartridges suitable for intended use should be used.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Light (or pale). Straw.

Odour Mild.

Odour threshold Not available.

Active XLS

pH (concentrated solution): ~ 13.1 pH (diluted solution): ~ 10.8 @ 1%

Melting point ~ 0°C

Initial boiling point and range ~ 100 @°C @ 760 mm Hg

Flash point Not applicable.

Evaporation rate Not available.

Upper/lower flammability or

explosive limits

Not applicable.

Vapour pressure Not applicable.

Vapour density Not applicable.

Relative density ~ 1.090 @ (20°C)°C

Solubility(ies) Soluble in water. Miscible with water.

Partition coefficient Not available.

Auto-ignition temperature Not applicable.

Decomposition Temperature Not available.

Viscosity ~ 1 cSt @ °C

Oxidising properties Not applicable.

Comments Information declared as "Not available" or "Not applicable" is not considered to be relevant to

the implementation of the proper control measures.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 0 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

products

15

No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid Acid anhydrides. Acids. Phenols, cresols.

10.6. Hazardous decomposition products

Hazardous decomposition

Does not decompose when used and stored as recommended. Thermal decomposition or

combustion products may include the following substances: Corrosive gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Active XLS

Toxicological effects No data recorded.

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 9,314.46

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC50) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Skin Corr. 1C - H314 Causes severe burns.

Human skin model test Scientifically unjustified.

Extreme pH ≥ 11.5 Corrosive.

Serious eye damage/irritation

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Corrosive to the respiratory tract. Symptoms following overexposure may include the

following: Severe irritation of nose and throat.

Ingestion May cause chemical burns in mouth, oesophagus and stomach. Symptoms following

overexposure may include the following: Severe stomach pain. Nausea, vomiting.

Active XLS

Skin contact Causes severe burns. Symptoms following overexposure may include the following: Pain or

irritation. Redness. Blistering may occur.

Eye contact Causes serious eye damage. Symptoms following overexposure may include the following:

Pain. Profuse watering of the eyes. Redness.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

Medical symptoms No specific symptoms noted, but this chemical may still have adverse health impact, either in

general or on certain individuals.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

trisodium nitrilotriacetate

Toxicological effects Nitrilotriacetic acid, trisodium salt (NTA) has caused kidney tumours in rats and

mice when administered orally in high concentrations. The tumours are based on

organ damage that can only occur when extremely high threshold limit

concentrations, as compared with possible human exposure, are exceeded. In view of the potential degree of exposure, there should be no cancer risk to humans.

Acute toxicity - oral

ATE oral (mg/kg) 500.0

Carcinogenicity

Carcinogenicity Limited evidence of a carcinogenic effect.

sodium hydroxide

Other health effects There is no evidence that the product can cause cancer.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Route of exposure Skin absorption Ingestion Skin and/or eye contact

Target organs No specific target organs known.

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Acute toxicity - oral

Acute toxicity oral (LD₅₀

2,000.0

mg/kg)

Species Rat

Notes (oral LD₅₀) Acute Tox. 4 - H302 Harmful if swallowed.

Acute toxicity - dermal

Active XLS

Acute toxicity dermal (LD₅₀ 2,001.0

mg/kg)

Species Rabbit

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 2,001.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Animal data Based on available data the classification criteria are not met.

Extreme pH Not applicable.

Serious eye damage/irritation

Serious eye

damage/irritation

Eye Dam. 1 - H318 Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Genotoxicity - in vivo Not determined.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity -Based on available data the classification criteria are not met.

fertility

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration

and the length of exposure.

Active XLS

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion May cause discomfort if swallowed. Stomach pain. Nausea, vomiting.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact Causes serious eye damage. Symptoms following overexposure may include the

following: Pain. Profuse watering of the eyes. Redness.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

SECTION 12: Ecological information

Ecotoxicity The product may affect the acidity (pH) of water which may have hazardous effects on aquatic

organisms.

Ecological information on ingredients.

sodium hydroxide

Ecotoxicity The product may affect the acidity (pH) of water which may have hazardous effects

on aquatic organisms.

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Ecotoxicity The product may affect the acidity (pH) of water which may have hazardous effects

on aquatic organisms.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic

invertebrates

Not determined.

Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms

Acute toxicity - terrestrial Not determined.

Ecological information on ingredients.

trisodium nitrilotriacetate

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 114-470 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 560-1,000 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

IC₅₀, 72 hours: 180-320 mg/l, Algae

sodium hydroxide

Acute aquatic toxicity

Active XLS

Acute toxicity - fish LC50, 48 hours: ~ 189 mg/l, Leuciscus idus (Golden orfe)

LC₅₀, 96 hours: 125 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: > 100 mg/l, Daphnia magna EC₅₀, 48 hours: 40-240 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

Not known.

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Toxicity Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: > 1 - 10 mg/l, Cyprinus carpio (Common carp)

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: > 1 - 10 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: > 1 - 10 mg/l, Freshwater algae

12.2. Persistence and degradability

Persistence and degradability The surfactant(s) contained in this product complies(comply) with the biodegradability criteria

as laid down in The Detergents Regulations (as amended).

Chemical oxygen demand ~ 81519 mg O₂/l

Ecological information on ingredients.

trisodium nitrilotriacetate

Persistence and

degradability

The product is biodegradable.

sodium hydroxide

Persistence and

degradability

The product contains only inorganic substances which are not biodegradable. The

product is potentially degradable.

Stability (hydrolysis) Not applicable.

Biological oxygen demand ~ 0 g O₂/g substance

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Persistence and

The surfactant(s) contained in this product complies(comply) with the

degradability

biodegradability criteria as laid down in The Detergents Regulations (as amended).

Biological oxygen demand ~ 0 g O₂/g substance

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

trisodium nitrilotriacetate

Active XLS

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

sodium hydroxide

Bioaccumulative potential The product is not bioaccumulating.

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is water-soluble and may spread in water systems. The product is non-volatile.

Ecological information on ingredients.

trisodium nitrilotriacetate

Mobility The product is soluble in water.

sodium hydroxide

Mobility The product is soluble in water.

Henry's law constantThe product contains mainly inorganic substances which are not biodegradable.

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Mobility The product is water-soluble and may spread in water systems. The product is non-

volatile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

trisodium nitrilotriacetate

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current UK criteria.

assessment

sodium hydroxide

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current UK criteria.

assessment

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current UK criteria.

assessment

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO)

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners

may retain some product residues and hence be potentially hazardous.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal

contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID) 1824

UN No. (IMDG) 1824

UN No. (ICAO) 1824

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

SODIUM HYDROXIDE SOLUTION

Proper shipping name (IMDG) SODIUM HYDROXIDE SOLUTION

Proper shipping name (ICAO) SODIUM HYDROXIDE SOLUTION

Proper shipping name (ADN) SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es)

ADR/RID class 8

ADR/RID label 8

IMDG class 8

ICAO class/division 8

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

Active XLS

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

IMDG Code segregation

18. Alkalis

group

EmS F-A, S-B

Emergency Action Code 2R

Hazard Identification Number 80

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

Guidance Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Only trained personnel should use this material. This product has been manufactured under

ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

Classification procedures

Eye Dam. 1 - H318: Skin Corr. 1C - H314: : Calculation method. Met. Corr. 1 - H290: : Expert

according to SI 2019 No. 720 judgement.

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Active XLS

Issued by Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire,

WS14 0DH, Great Britain.

www.autosmartinternational.com

rbutler@autosmart.co.uk Tel +44 (0)1543 481616

Revision date 16/09/2022

Revision 12

SDS status

Supersedes date 21/10/2019

Hazard statements in full H290 May be corrosive to metals.

Approved.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eye irritation. H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.