

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : (Aerosol) Satin Black
UFI : 3N5X-G0KF-600H-5K6F
Product code : 003498000019
Type of product : Paint
Vaporizer : Aerosol
Synonyms : ASBL001D

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only
Use of the substance/mixture : Spraying paint (spray can)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

AUTOSMART INTERNATIONAL
9 Attwood Road
WS7 3GJ Burntwood, Staffordshire, ENGLAND
T +44 (0) 1543 481616 (09:00 - 17:00)
SHREQ@autosmart.co.uk, www.autosmartinternational.com

1.4. Emergency telephone number

Emergency number : NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident),
Call NCEC at +44 1865 407333 (24Hrs UK)
when calling please quote "AUTOSMART 29003-NCEC"

If you urgently need medical help or advice but it's not a life-threatening situation, call 111 free from any phone to speak to an NHS adviser. The 24-hour NHS 111 service can give you healthcare advice or direct you to the local service that can help you best.

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.

(Aerosol) Satin Black


Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: Acetone; n-butyl acetate

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing vapours, spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Acetone substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	24.9 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) substance with national workplace exposure limit(s) (BE, CZ, GB, GR, HR) (Note K)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6	24.9 – 50	Flam. Gas 1A, H220 Press. Gas
n-butyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, IS, MK, RS, CH); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	0.6995 – 2.798	Flam. Liq. 3, H226 STOT SE 3, H336
1-methoxypropan-2-ol substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	0.6995 – 2.798	Flam. Liq. 3, H226 STOT SE 3, H336
Di-"isononyl" phthalate substance with national workplace exposure limit(s) (CZ, DK, GB, HR, IE, IS)	CAS-No.: 28553-12-0 EC-No.: 249-079-5	0.2798 – 0.6995	Not classified
Carbon black substance with national workplace exposure limit(s) (BE, CZ, DK, ES, FI, FR, GB, GR, HR, HU, IE, PL, PT, IS, NO)	CAS-No.: 1333-86-4 EC-No.: 215-609-9 REACH-no: 01-2119384822-32	0.2798 – 0.6995	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	≤ 0.2798	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
-----------------------------------	--

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials	: Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m ³
	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m ³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m ³
	50 ppm
IOEL STEL	723 mg/m ³
	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA)	724 mg/m ³

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

n-butyl acetate (123-86-4)	
	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m ³
	50 ppm
IOEL STEL	550 mg/m ³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA)	274 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	548 mg/m ³
	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
1-methoxypropan-2-ol (107-98-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	1-Methoxypropanol-2
IOEL TWA	375 mg/m ³
	100 ppm
IOEL STEL	568 mg/m ³
	150 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropan-2-ol
WEL TWA (OEL TWA)	375 mg/m ³
	100 ppm
WEL STEL (OEL STEL)	560 mg/m ³
	150 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

1-methoxypropan-2-ol (107-98-2)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Di-"isononyl" phthalate (28553-12-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Diisononyl phthalate
WEL TWA (OEL TWA)	5 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Carbon black (1333-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Carbon black
WEL TWA (OEL TWA)	3.5 mg/m ³
WEL STEL (OEL STEL)	7 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOEL TWA	192 mg/m ³
	50 ppm
IOEL STEL	384 mg/m ³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
United Kingdom - Occupational Exposure Limits	
Local name	Toluene
WEL TWA (OEL TWA)	191 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m ³
	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Liquefied petroleum gas
WEL TWA (OEL TWA)	1750 mg/m ³
	1000 ppm
WEL STEL (OEL STEL)	2180 mg/m ³
	1250 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves					EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -40 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: < 20.5 mm²/s
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 644 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4

2-methoxy-1-methylethyl acetate (108-65-6)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
-----------------	--

1-methoxypropan-2-ol (107-98-2)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
-----------------	---

Di-"isononyl" phthalate (28553-12-0)

LD50 oral rat	> 10000 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Animal sex: female
LC50 Inhalation - Rat	> 4.4 mg/l air Animal: rat, Guideline: other:, Remarks on results: other:

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Di-"isononyl" phthalate (28553-12-0)

NOAEL (chronic, oral, animal/male, 2 years)	88.3 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OTS 798.3300 (Carcinogenicity), Remarks on results: other:
NOAEL (chronic, oral, animal/female, 2 years)	108.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.3300 (Carcinogenicity), Remarks on results: other:

Reproductive toxicity : Not classified

Di-"isononyl" phthalate (28553-12-0)

NOAEL (animal/female, F1)	200 – 260 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:, Guideline: EPA OTS 798.4700 (Reproduction and Fertility Effects)
---------------------------	---

STOT-single exposure : May cause drowsiness or dizziness.

Acetone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

n-butyl acetate (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

2-methoxy-1-methylethyl acetate (108-65-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

1-methoxypropan-2-ol (107-98-2)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

STOT-repeated exposure : Not classified

2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
1-methoxypropan-2-ol (107-98-2)	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Di-"isononyl" phthalate (28553-12-0)	
NOAEL (dermal, rat/rabbit, 90 days)	≈ 500 mg/kg bodyweight Animal: rabbit
Carbon black (1333-86-4)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0071 mg/l air Animal: rat, Animal sex: male
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0011 mg/l air Animal: rat, Animal sex: male
Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
Aspiration hazard : Not classified	
(Aerosol) Satin Black	
Vaporizer	Aerosol
Viscosity, kinematic	< 20.5 mm²/s
Not able to form a pool	Yes
1-methoxypropan-2-ol (107-98-2)	
Viscosity, kinematic	1.848 mm²/s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Acetone (67-64-1)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

n-butyl acetate (123-86-4)	
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
1-methoxypropan-2-ol (107-98-2)	
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:
Di-"isononyl" phthalate (28553-12-0)	
LC50 - Fish [1]	> 102 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 74 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 88 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
Carbon black (1333-86-4)	
EC50 72h - Algae [1]	> 10000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 10000 mg/l Test organisms (species):
12.2. Persistence and degradability	
(Aerosol) Satin Black	
Persistence and degradability	Not rapidly degradable
Acetone (67-64-1)	
Persistence and degradability	Not rapidly degradable
n-butyl acetate (123-86-4)	
Persistence and degradability	Not rapidly degradable
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Not rapidly degradable
1-methoxypropan-2-ol (107-98-2)	
Persistence and degradability	Not rapidly degradable
Di-"isononyl" phthalate (28553-12-0)	
Persistence and degradability	Not rapidly degradable
Carbon black (1333-86-4)	
Persistence and degradability	Not rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Not rapidly degradable

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
---------------------------	------

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content : 644 g/l

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Abbreviations and acronyms:

OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas	Gases under pressure
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

(Aerosol) Satin Black

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Full text of H- and EUH-statements:

STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
-----------	--

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.