

Document Information:

COSHH ASSESSMENT Assessment No. C1029 Substance Name: C1029 - Aquawax - Product NO.475-9 Assessed By: Craig Carswell Supplier: Autosmart International Ltd Date: 14/04/2025 Next Review: 14/04/2026 Location: Carswells Devil in the Detail

Assessment No. C1029
Aquawax - Product N0.475-9
Craig Carswell (Carswells Devil in the Detail)
14/04/2025
Autosmart International Ltd
01543 481616 (09:00 - 17:00)
Rinse aid - Wax
Inhalation: Prolonged inhalation of high concentrations may damage respiratory system. **Ingestion:** May cause irritation. **Skin Contact:** Redness and irritation can occur. **Eye Contact:** Can be irritating to eyes.
Skin irritant.2, Eye irritant.2
LOW
No
Inhalation =, Ingestion =, Absorption (Skin) =, Eye Contact =, Injection =
Protective Clothing ©, Gloves ©, Anti-static Footwear □, Respiratory Protection □, Eye Protection ©
Harmful
H315 Causes skin irritation. H319 Causes serious eye irritation.
P264 Wash contaminated skin thoroughly after handling. P280 Wear eye protection and protective gloves. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362+P364 Take off contaminated clothing and wash. P501 Dispose of contents/container in accordance with national regulations.
Quantity Stored: 20 Itr (maximum 50 Itr). **Quantity Used Per Week:** 50 Itr (max). **Application:** Siphoned from the main barre into a 10-litre drum for Carwash use. The car wash hose is connected, and the substance is drawn up, diluted, and used as needed. Also used in hand wash by spraying onto a wet car and wiping down with a cloth.
2-BUTOXYETHANOL: 123mg/m3 (25ppm) long-term, 246mg/m3 (50ppm) short-term. **PROPAN-2-OL:** 999mg/m3 (400ppm) long- term, 1250mg/m3 (500ppm) short-term.
APF 20/FFP3 rated if needed (not normally in use with this product).
Follow manufacturer's recommendations. Store in original container, tightly sealed, and in a cool, well-ventilated place. Avoid contact with eyes and inhalation of vapours. Keep out of reach of unauthorized personnel. Avoid spraying near stairs or gangways.
Do not take action without proper training or safety precautions. Avoid inhalation of vapours and dust. Wear protective clothing and use suitable respiratory protection. Inform authorities of environmental pollution if large spillages occur. Clean up and dispose of waste as per local regulations.
Colour-coded substance boards in wash and valeting bays to prevent mix-ups. PPE is available and used. Limits on quantities stored on-site. Product kept in bunded trays or cabinets. Product may be hazardous to aquatic life under CLP.
^{**I} Inhalation: ^{**} Move affected person to fresh air, maintain an open airway, and keep warm. ^{**} Skin Contact: ^{**} Rinse with plenty of water ^{***} Eye Contact: ^{**} Rinse with water for at least 10 minutes. ^{***} Ingestion: ^{***} Rinse mouth, give water or milk to drink, and seek medical help if necessary.



Document Information:

COSHH ASSESSMENT Assessment No. C1029 Substance Name: C1029 - Aquawax - Product NO.475-9 Assessed By: Craig Carswell Supplier: Autosmart International Ltd Date: 14/04/2025 Next Review: 14/04/2026 Location: Carswells Devil in the Detail

NAME	Date	SIGNATURE
Craig Carswell	14/04/2025	Call