

Cover Sheet

Attention: Prospective Bidders

Date: 4/12/2022

Company: _____

Number of Pages (Including Cover): 5

Fax Number: _____

Voice Number: _____

From: Paul Witherel

Subject: BID#2024-04 2023 CDBG Underhill Park Improvements – Clarification

Comments:

Please Find Attached Clarification No. 1.

April 12, 2024

RE: Bid Clarification #1
BID#2024-04
2023 CDBG Underhill Park Improvements
Hamilton Twp, Atlantic County, NJ
MWA # 5500.7

Attention: Prospective Bidders

Please note the following Clarifications:

1. Updated Technical Specification pages TS 31-32 regarding Item No.'s 8-11, S2-1 & S2-2.

Please sign and return via fax the attached Bid Clarification receipt form. **All bids are still due on Thursday, April 25th at 10:00am.**

Please note that any further RFI's must be submitted by 5:00pm on Monay, April 22nd.

Very truly yours,

MOTT WATKINS ASSOCIATES, LLC



Paul Witherel, E.I.T.

ITEM NO. S2-1 – CHAIN LINK FENCE , 4’ HIGH

ITEM NO. 8 – CHAIN LINK FENCE , 6’ HIGH

ITEM NO. 9 – CHAIN LINK FENCE , 8’ HIGH

ITEM NO. 10 – CHAIN LINK FENCE , 16’ HIGH

ITEM NO. S2-2 – CHAIN LINK FENCE – GATE 4’ HIGH 6’ WIDE

ITEM NO. 11 – CHAIN LINK FENCE – SLIDE GATE 6’ HIGH

Section 614.01 - Description

The Contractor shall furnish all labor, material, equipment, etc., for the installation of a chain link fence, complete in place with gates, as shown on the plans and as herein specified and directed by the Engineer. **Mobilization and layout for this item shall be included in bid. The restoration, in kind, of the existing ground that is disturbed as a result of the installation of the proposed fence shall be included in the unit price for each fence type.**

Section 614.02 - Materials

Chain link fence, as referred to in these specifications, shall consist of galvanized steel fabric and galvanized steel post, including gates constructed on bases.

Fabric - Wire fabric shall be as follows:

- a) 4- and 6-foot-high fence shall be No. 9 gauge black vinyl coated steel wire woven to a 2 inch mesh with top and bottom salvages knuckled.
- b) 8-foot-high fence shall be No. 8 2a gauge black vinyl coated steel wire woven to a 2 inch mesh with top and bottom salvages knuckled.
- c) 16-foot-high fence shall be No. 6 gauge black vinyl coated steel wire woven to a 2 inch mesh with top and bottom salvages knuckled.
- d) Dugout faces shall have 1-3/4” Open x 9 gauge x 8’ high black vinyl coated mesh.

Terminal/Corner Posts- All corner and end posts shall be 2.5” O.D. “Standard Weight” pipe, 5.79 pounds per linear foot for 4- and 6-foot-high fence, 3.0” O.D. for 8-foot-high fence.

Intermediate Posts – Intermediate posts may be 2.0” O.D. nominal galvanized steel pipe, 2.70 lbs. per linear foot for 4- and 6-foot-high fence, 2.5” O.D. for 8-foot-high fence.

Rails & Braces – Top rails and middle rails shall be 1 5/8” O.D. standard weight galvanized pipe, 2.27 lbs. Per linear foot. Middle rails only required for 12’ high fence or higher.

Galvanizing – All posts and other appurtenances used in construction of the fence shall be hot dipped or electrogalvanized steel, or other non-corrosive metal. The zinc coating on all fabric and wire shall weigh not less than 1.2 ounces per square foot of surface area.

Ornaments – All posts, where designated, are to be equipped with malleable, cast iron or pressed steel ornamental tops. Tubular post tops to be so designed as to exclude moisture from the post. All intermediate post tops to be designed to hold the top rail.

Back Stops – Fabric shall be the same as for the dugout faces. 2 runs of 8’ high mesh for 16’ chain link fence. End, line and corner posts shall be 4” O.D. standard weight galvanized pipe with concrete footings. Top, middle and bottom rails are to be 1-5/8” O.D.

Gates – Gates (both slide and swing) shall be installed with industrial hardware. Swing gates shall include all hardware for an operational gate to swing both ways.

Section 614.04 - Construction

Fence and gates shall be erected in accordance with the construction requirements recommended by the manufacturer and the following:

Terminal posts shall be set at the beginning and end of each continuous length of fence, at abrupt changes in vertical and horizontal alignment and on each side of gate locations. Aluminum surfaces to be placed in contact with concrete shall be given a coat of zinc chromate primer.

Posts to be set in concrete shall be installed in dug or predrilled holes. Posts not requiring concrete foundation may be driven to the required depth if ground conditions permit or the posts shall be installed in holes dug or drilled to allow room for backfilling.

Post holes for posts not requiring concrete foundations shall be backfilled with suitable material. Backfill shall be placed in layers not exceeding 4 inches and each layer shall be thoroughly tamped.

Pull shall not be applied to posts set in concrete foundations until the concrete has cured a minimum of 72 hours.

Gates shall be equipped with locks and two (2) sets of keys.

Section 614.07 - Method of Measurement

Fence of the various kinds and sizes will be measured by the linear foot along the bottom line of the fence.

Section 614.08 - Basis of Payment

Payment will be made under:

Pay Item	Pay Unit
Chain Link Fence, 4' High	Linear Foot
Chain Link Fence, 8' High	Linear Foot
Chain Link Fence, 12' High	Linear Foot
Chain Link Fence, 16' High	Linear Foot
Chain Link Fence – Gate 4' High 6' Wide	Unit
Chain Link Fence – Slide Gate 6' High	Unit

Payment for this Item, for the quantity as above determined at the unit price bid in the proposal, which price shall include, but not necessarily be limited to the cost of all materials, delivery, excavation, placement, grading, compaction, rods, pipe, concrete, wire, etc., all as described including all labor, equipment, supervision, and all else necessary therefore and incidental thereto for a complete installation.

Fax to: 609-569-1521
Or
E-mail to: info@mottwatkins.com

Bid Clarification #1 Receipt Verification
BID#2024-04 – 2023 CDBG Underhill Park Improvements

I verify that I have received the Bid Clarification Documents, Five (5) pages,
Dated April 12, 2024.

Signature

Date

Name

Company