

PRODUCT DESCRIPTION

Dymonic® FC is a high-performance, fast-curing, single-component, low modulus, hybrid sealant formulated with proprietary silane end-capped polymer technology.

DYMONIC FC STANDARD COLORS



APPLICABLE STANDARDS

ASTM C 920 Type S, Grade NS, Class 35, Use NT, M, A and O; ASTM C 1248; CAN/CGSB-19.13-M87; U.S. Federal Specification TT-S-00230C, Class A, Type II; Meets AAMA 808.3-10; UL 2079 (ASTME 1966), CAN-4-S115M.

Colors shown are approximate and may not reflect the shade precisely. Different lighting conditions can influence color appearance, for truer color please view in daylight. Colors vary by package sizes. Custom colors and alternate packaging available. Contact Tremco Customer Service for more information.

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.

Tremco® and Dymonic® are registered trademarks of Tremco Incorporated. Willseal is a registered trademark of Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.

Part of

Construction Products Group