

CleanGreen®



Microbial Wastewater Digester

Principal Functioning Agent:

Microbes (microorganisms or bacterium in aerobic format that will transform into anaerobic depending on the substance being consumed).

General Use Directions

BioTec is a 100% microbial digester designed to break down excrements, bloods, and organic matters found in septic tanks, lagoons, and wastewater digester tanks while increasing healthy bacterium activity and raising oxygen levels.



Recommended Application Rates

BioTec should be used initially through the lift station on the septic lagoon and/or aeration tank with the worst sludge build-up. Once sludge levels are lowered, a maintenance application should be subsequently used.

BioTec should be used at an initial application rate of 200 gallons per linear acre (43,560 sq. ft.). A maintenance application rate of BioTec should be used at 1 gallon per linear acre.

***NOTE: BioTec will be ineffective if just flushed through system.** The microbial package is meant to be agitated and left to digest waste and sludge until desired levels are met. Do not remove or flush prematurely.

Caution: Keep out of reach of children.

Harmful if swallowed. If ingested, consult a physician immediately. Avoid prolonged contact with skin. In case of eye contact, flush with plenty of water for at least 15 minutes. If irritation persists, consult a physician.

Gallons: _____ Net Weight: 8.5 lb. per gallon

U.S. Ag, LLC makes no warranties of any kind, express or implied with respect to CleanGreen® BioTec. Manufacturer's and seller's obligation limited to replacement of product for defective material only. Neither seller or manufacturer shall be liable for any injury, loss, or damage directly or consequently arising from the misuse or inability to use the product.

U.S. Ag Industrial

PO Box 368
Hogansville, GA 30230

Phone: (706) 637-1111

www.usagindustrial.com