

# CleanGreen®



## Principal Functioning Agent:

Microbes (microorganisms or bacterium in aerobic format that will transform into anaerobic depending on the substance being consumed).

## General Use Directions

BioTec is a 100% microbial digester designed for bioremediation and wastewater treatment to break down human and animal excrements, bloods, and organic matters found in septic tanks, lagoons, and wastewater digester tanks while also increasing healthy bacterium activity and raising oxygen levels.



## Recommended Application Rates

BioTec should be used initially on the septic lagoon and/or aeration tank with the worst sludge build-up. Once sludge levels are lowered, a maintenance application should be subsequently used.

BioTec should be used at an initial application rate of 200 gallons per linear acre (43,560 sq. ft.). A maintenance application rate of BioTec should be used at 1 gallon per linear acre.

### **\*BioTec will be ineffective if just flushed through system.**

The microbial package is meant to be agitated and left to digest sludge in tanks and lagoons until levels are acceptable.

### **Caution: Keep out of reach of children.**

Harmful if swallowed. If ingested, consult a physician. Avoid prolonged contact with skin. In case of eye contact, flush with plenty of water for at least 15 minutes.

Gallons: \_\_\_\_\_ Net Weight: 8.5 lb. per gallon

U.S. Ag Industrial is a subsidiary of U.S. Ag, LLC. U.S. Ag, LLC makes no warranties of any kind, express or implied with respect to CleanGreen® BioTec. Manufacturer's and seller's obligation limited to replacement of product for defective material only. Neither seller or manufacturer shall be liable for any injury, loss or damage directly or consequently arising from the misuse or inability to use the product.

**U.S. Ag Industrial**  
**PO Box 807**  
**Hogansville, GA 30230**  
**Phone: (706) 616-5487**  
**www.usagindustrial.com**