

# CleanGreen®

## BORTEC



### Principal Functioning Agent:

Soap (the water soluble sodium or potassium salts of fatty acids produced by either the saponification of fats and oils, or the neutralization of fatty acid).

### General Use Directions

BorTec is a 100% biodegradable, non-ionic surfactant designed to improve the performance of oil pumps and other petroleum equipment by effectively dissolving paraffin build-up and oil fissure clots. It can also be used as a rig wash and to clean oil spills.



### Recommended Application Rates

BorTec should be used at 100% concentration for wellbore cleaning, and then a 3:1 ratio for cleaning of rigs and oil spills.

Product can be applied by hand, through a hand sprayer, pump sprayer, hose attachment, or as a wash dip.

Rate of 50 gallons of BorTec per wellbore of average length. Pour down well pipe and circulate for 48 hours. After circulation, allow contents to drain down into reservoir.

Spray BorTec 3:1 solution to clean rigs and spills as needed.

### Caution: Keep out of reach of children.

Harmful if swallowed. If ingested, consult a physician. Avoid prolonged contact with skin. In case of eye contact, flush with plenty of water for at least 15 minutes.

Gallons: \_\_\_\_\_ Net Weight: 8.75 lb. per gallon

U.S. Ag Industrial is a subsidiary of U.S. Ag, LLC. U.S. Ag, LLC makes no warranties of any kind, express or implied with respect to CleanGreen® BorTec. Manufacturer's and seller's obligation limited to replacement of product for defective material only. Neither seller or manufacturer shall be liable for any injury, loss or damage directly or consequently arising from the misuse or inability to use the product.

**U.S. Ag Industrial**  
**PO Box 807**  
**Hogansville, GA 30230**  
**Phone: (706) 616-5487**  
**www.usagindustrial.com**