


New from GC Valves  
**NSF-61 CERTIFIED**  
**¾" & 1" NPT**  
**SOLENOID VALVES**



***Our Reinforced Nylon body with EPDM seals is now available with NSF-61 certification for drinking water.***

**New from GC Valves** – introducing Lead-Free solenoid valves with NSF-61 certification: part of the C4 and C9 Series from our Components For Automation product line.

**For application in:**

- Drinking Water Systems
- Food & Beverage
- Reverse Osmosis
- Scientific Equipment
- Restaurants
- Municipal Installations
- Ultra-Violet Water Treatment
- Industrial Products
- Grocery Stores
- Commercial Projects
- Misting
- Residential Water

**Lead-Free Solenoid Valves with NSF-61 Certification**

Body: Reinforced Nylon

Seals: EPDM

Operation: 2-way Normally Closed  
(energize to open)

Operator Materials: 300 & 400 Series  
Stainless Steel

Operating Pressures:

Minimum - 4 psi

Maximum - 150 psi

Operating Temperatures:

Ambient - 32 to 125 ° F

Ports: ¾" & 1" NPT (BSPT optional)

Cv: 6.7 & 13

Standard Voltages: 24, 120, 240 AC  
60hz (50hz optional); 6, 12, 24 DC

Voltage Tolerance: + or - 10%

Standard Housing: DIN (NEMA 4 with  
optional connector)

Optional Housing: 12" leads

Optional Connectors: DIN, Lighted  
DIN, ½" Conduit Hub, Surge  
Protection

Optional Cord: 6 foot cord with 2- or  
3-prong wall plug

Mounting Position: Any

**GC Valves, LLC., A DEMA Company**

456 Crompton Street | Charlotte, NC 28273

800.828.0484 | 704.588.3300 | fax 704.973.9526 | [service@gcvalves.com](mailto:service@gcvalves.com)

[www.gcvalves.com](http://www.gcvalves.com) | [www.cfa-inc.com](http://www.cfa-inc.com) | [www.demaeng.com](http://www.demaeng.com)