

# SOLENOID VALVES FOR HOT WATER & STEAM

1/8" TO 2" NPT NORMALLY CLOSED & NORMALLY OPEN

## Teflon Seals



S30 & S31 Direct Acting  
1/8", 1/4", 3/8"  
Brass or Stainless Steel  
0 to 2400 psi Water  
0 to 150 psi Steam



S40 Piloted Piston  
1/4", 3/8", 1/2"  
Brass or Stainless Steel  
0 to 300 psi Water  
0 to 150 psi Steam



S21..T4 Piloted Diaphragm  
3/8", 1/2", 3/4"  
Brass  
10 to 250 psi Water  
10 to 100 psi Steam



S21..T2 Piloted Diaphragm  
3/8", 1/2", 3/4"  
Brass  
10 to 150 psi Water  
10 to 150 psi Steam



S21 Piloted Diaphragm  
1" to 2"  
Brass or 316 Stainless Steel  
10 to 150 psi Water  
10 to 150 psi Steam

# Hot Water & Steam

1/8" TO 2" NPT NORMALLY CLOSED & NORMALLY OPEN

## EPR Seals



C9 & C4 Direct Acting  
1/8", 1/4", 3/8"  
Brass or 316 Stainless Steel  
0 to 2030 psi Water  
0 to 50 psi Steam



S30 & S31 Direct Acting  
1/4", 3/8", 1/2"  
Brass or Stainless Steel  
0 to 2400 psi Water  
0 to 50 psi Steam



S40 Piloted Piston  
1/8", 1/4", 3/8"  
Brass or Stainless Steel  
0 to 300 psi Water  
0 to 50 psi Steam



S21 Piloted Piston  
3/8" to 2"  
Brass or 316 Stainless Steel  
4 to 150 psi Water  
4 to 50 psi Steam



S20 Zero Differential  
3/8" to 1-1/2"  
Brass or 316 Stainless Steel  
0 to 140 psi Water  
0 to 50 psi Steam



S27 Zero Differential  
1" to 2"  
Brass or 316 Stainless Steel  
0 to 100 psi Water  
0 to 50 psi Steam

### Other 2- & 3-way Designs:

- Bodies - Stainless Steel, Brass, Polypropylene, Nylon, Noryl, others
- Seals - Nitrile, Viton, EPR, Teflon, Rulon, FFKM, Santoprene, others
- Electrical - All Common AC & DC Voltages
- Housings - Conduit, DIN, NEMA 7/9 Explosion Proof, Junction Box, Open Frame Leads
- Manifolds - wide variety of standard products; designed to meet custom applications
- Approvals - UL, CSA, CE, NSF

