



**LIFT
INSPECTIONS**

NORTHWEST

An Auto Dealer Compliance LLC Company

DAILY PRE-USE INSPECTION CHECKLIST

2 POST ABOVE GROUND AUTO-LIFT

AUTO-LIFT SERIAL#:

LIFT LOCATION:

TECHNICIANS NAME:

LOCATION ADDRESS:

Refer to illustration in the inspection binder for visual guidelines.

Do not operate this auto-lift if an unsafe condition is discovered.

Lock/Tag the auto-lift out of service and notify your supervisor immediately.

INSPECTED BY																			
	DATE																		

#	Equipment Description and Inspection Criteria	✓ = Satisfactory	U = Unsatisfactory	N = Not Applicable															
1	Check for accessibility and readability of the operating procedures, lift manuals, applicable safety instructions, safety warning labels and load capacity labels.																		
2	Ensure that there is adequate clearance around the lift.																		
3	Check for proper operation of the lift controls and locking devices.																		
4	Inspect arm restraints to verify proper operation and engagement.																		
5	Verify that latch covers are installed.																		
6	Verify that arm stop is installed to prevent the inner arms from sliding out.																		
7	If present, inspect equalizer cables for frays, stretching, corrosion and proper cable adjustment.																		
8	Check for damage or excessive wear of other components such as hoses, electrical wires, drive chains, cables or screws. Verify that hoses and cables are routed properly, not kinked and not rubbing.																		
9	Check for damage or excessive wear on any of the lifting-adapter contact points which engage the vehicle during lift.																		
10	Check for evidence of hydraulic or pneumatic leaks.																		
11	Check hydraulic fluid for contamination and proper fill levels.																		
12	Check for unusual noises, erratic operations or evidence of chips or filings during use.																		
13	Inspect sheaves to make sure they are turning freely and to make sure shields are in place.																		
14	Check for cracks or loose concrete around floor anchor bolts.																		

NOTES/COMMENTS: _____
