

Test Verification of Conformity

Verification Number: 210400878SHA-V1

On the basis of the referenced test report(s), sample(s) tested of the below product have been found to comply with the standards harmonized with the directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it <them>.

Once compliance with all product relevant  mark directives are verified, including any relevant e.g. risk assessment and production control, the manufacturer may indicate compliance by signing a Declaration of Conformity themselves and applying the mark to products identical to the tested sample(s).

Applicant Name & Address:	Afore New Energy Technology (Shanghai) Co., Ltd Build No.7, 333 Wanfang Road, Minhang District, Shanghai. China. 201112
Product Description: Ratings & Principle Characteristics:	PV Grid interactive inverter See Appendix
Models/Type References:	HNS3000TL, HNS3600TL-1, HNS3600TL, HNS4000TL, HNS5000TL, HNS6000TL, HNS7000TL, HNS8000TL, HNS9000TL, HNS10000TL
Brand Name:	Afore
Relevant Standards/Directives:	IEC/EN 62109-1:2010 (First Edition) IEC/EN 62109-2:2011 the Low Voltage Directive 2014/35/EU
Verification Issuing Office Name & Address:	Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China
Date of Tests:	2021-09-15 to 2021-11-20
Test Report Number(s):	210400878SHA-001/002

Signature



Name: Jonny Jing
Position: Manager
Date: 2021-12-06

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

APPENDIX: Test Verification of Conformity

This is an Appendix to Test Verification of Conformity Number: 210400878SHA-V1

Ratings:

Specifications table					
Model	HNS3000TL	HNS3600TL-1	HNS3600TL	HNS4000TL	HNS5000TL
Input:					
Vmax PV (Vdc)	600	600	600	600	600
Isc PV (absolute Max.) (A)	18 x 2	18	18 x 2	18 x 2	18 x 2
Number MPP trackers	2	1	2	2	2
Number input strings	1/1	1	1/1	1/1	1/1
Max. PV input current(A)	14 x 2	14	14 x 2	14 x 2	14 x 2
MPPT voltage range (Vdc)	70-550	70-550	70-550	70-550	70-550
Vdc range @ full power (Vdc)	110-550	265-550	130-550	145-550	180-550
Output					
Normal Voltage(V)	L/N/PE, 220Vac, 230Vac, 240Vac				
Frequency (Hz)	50 / 60				
Current (normal) (A)	13.1	15.7	15.7	17.4	21.8
Current (Max. continuous) (A)	15	17.5	17.5	20	24
Power rating (W)	3000	3600	3600	4000	5000
Power Rating (VA)	3000	3600	3600	4000	5000
Power factor /rated	1 (-0,8~+0,8 adjustable)	1 (-0,8~+0,8 adjustable)	1 (-0,8~+0,8 adjustable)	1 (-0,8~+0,8 adjustable)	1 (-0,8~+0,8 adjustable)
others					
Protective class	Class I				
Ingress protection (IP)	IP 65				
Temperature (°C)	-25°C to +60°C (up 45°C derating)				
Inverter Isolation	Non-isolated				
Overvoltage category	OVC III (AC Main), OVC II (PV)				
Weight (kg)	10				
Dimensions (WxHxD) (mm)	358x360x142				

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Specifications table					
Model	HNS6000TL	HNS7000TL	HNS8000TL	HNS9000TL	HNS10000TL
Input:					
Vmax PV (Vdc)	600	600	600	600	600
Isc PV (absolute Max.) (A)	18 x 2	18+35	18+35	35 x 2	35 x 2
Number MPP trackers	2	2	2	2	2
Number input strings	1/1	1/2	1/2	2/2	2/2
Max. PV input current(A)	14 x 2	14+26	14+26	26 x 2	26 x 2
MPPT voltage range (Vdc)	70-550	70-550	70-550	70-550	70-550
Vdc range @ full power (Vdc)	220-550	220-550	220-550	220-550	220-550
Output					
Normal Voltage(V)	L/N/PE, 220Vac, 230Vac, 240Vac				
Frequency (Hz)	50 / 60				
Current (normal) (A)	26.1	30.5	34.8	39.2	43.5
Current (Max. continuous) (A)	28.7	33.6	38.3	45	50
Power rating (W)	6000	7000	8000	9000	10000
Power Rating (VA)	6000	7000	8000	9000	10000
Power factor /rated	1 (-0,8~+0,8 adjustable)	1 (-0,8~+0,8 adjustable)	1 (-0,8~+0,8 adjustable)	1 (-0,8~+0,8 adjustable)	1 (-0,8~+0,8 adjustable)
others					
Protective class	Class I				
Ingress protection (IP)	IP 65				
Temperature (°C)	-25°C to +60°C (up 45°C derating)				
Inverter Isolation	Non-isolated				
Overvoltage category	OVC III (AC Main), OVC II (PV)				
Weight (kg)	17			18	
Dimensions (WxHxD) (mm)	510 x 370 x 192			535x370x192	

Signature



Name: Jonny Jing
Position: Manager
Date: 2021-12-06

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.