

Issuing Date 15-Apr 2015 Revision Date 30-Apr 2015 Revision Number 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product SDS Name Silicone Sealant – Oxime - Grey

J-B Weld FG SKU Part Numbers Covered

32327, 32507, 32927

J-B Weld Product Names Covered

Ultimate Grey (all sizes)

Water Pump & Thermostat (all sizes)

J-B Weld Product Type

Silicone - Oxime Grade

Recommended use of the chemical and restrictions on use

Recommended Use Automotive Sealant & Gasket Maker

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name J-B WELD COMPANY, LLC

Supplier Address 1130 COMO ST

SULPHUR SPRINGS, TX 75482

USA

Emergency Telephone Numbers Transportation Emergencies: Chemtrec (24 hour transportation emergency response info):

800-424-9300 or 703-527-3887

Poison/Medical Emergencies: Poison Control Centers (24 hour emergency poison / medical

response info): 800-222-1222

Supplier Email <u>info@jbweld.com</u>

Supplier Phone Number 903-885-7696



2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Skin sensitization	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Warning

Hazard Statements

Causes skin and eye irritation May cause an allergic skin reaction



Appearance Dark gray/black

Physical State Solid Gel Consistency Solid

Odor Slight

Precautionary Statements - Prevention

Wear eye/face protection

Wear protective gloves

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Eyes

Direct eye contact irritates slightly with redness and swelling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

A single short term exposure (less than 24 hours) may irritate. Repeated prolonged contact (24 to 48 hours) may irritate moderately. Product contains oximes which are possible skin sensitizers. IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention

Inhalation

Vapor overexposure may cause drowsiness. There are no known effects associated with prolonged and/or repeated exposure.

Ingestion

Small amounts transferred to the mouth by fingers during use, etc. should not injure. Swallowing large amounts may injure slightly.

Precautionary Statements - Storage

None



Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

1% of the mixture consists of ingredient(s) of unknown toxicity

Other information

No information available

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Calcium Carbonate	1317-65-3	50
Silica	7631-86-9	10
2-Butanone, O,O`,O``-(methylsilylidyne)trioxime	22984-54-9	4
Carbon black	1333-86-4	<1
3-(Triethoxysilyl) propylamine	919-30-2	<1
2-Butanone, O,O`,O``-(ethenylsilylidyne)trioxime	2224-33-1	<1
Polydimethylsiloxane	63148-62-9	15
Dimethyl Siloxane	70131-67-8	18

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. If symptoms persist,

call a physician.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. May

cause an allergic skin reaction. In the case of skin irritation or allergic reactions

see a physician.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

IngestionDo NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Use personal protective equipment as

required.

Most important symptoms and effects, both acute and delayed



Revision Date 30-Apr-2015

Most Important Symptoms and Burning sensation. Itching. Rashes. Hives.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Uniform Fire Code Sensitizer: Solid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.



7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off

contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone 1317- 65-3	-	TWA: 15 mg/m ³ TWA: 5 mg/m ³ (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³	TWA: 5 mg/m³ respirable dust TWA: 10 mg/m³ total dust
Silica 7631-86-9	-	TWA: 20 mppcf : (80)/(% SiO2) mg/m³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Carbon black 1333- 86-4	TWA: 3 mg/m³ inhalable fraction	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If there is a risk of contact:. Wear safety glasses with side shields (or goggles).

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene MeasuresHandle in accordance with good industrial hygiene and safety practice. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing.

contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Solid Gel Consistency Solid

Appearance Dark gray/black Odor Slight

Color No information available Odor Threshold No information available

None known

<u>Property</u> <u>Values</u> <u>Remarks/ Method</u>

None known pН Neutral Melting / freezing point No data available None known No data available None known Boiling point / boiling range Flash Point >212 C >39.3 C None known No data available None known **Evaporation Rate** Flammability (solid, gas) Non-Flammable None known

Flammability Limit in Air
Upper flammability limit
No data available

Lower flammability limitNo data availableVapor pressureNo data availableNone knownVapor densityNo data availableNone known

None known **Specific Gravity** 1.38 None known Water Solubility Insoluble in water No data available None known Solubility in other solvents None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known

Kinematic viscosity

Dynamic viscosity

Explosive properties

Oxidizing Properties

No data available
No data available
No data available

Other Information

Softening Point No data available VOC Content (%) <3%

Particle Size No data available

Particle Size Distribution



10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

.

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye Contact Specific test data for the substance or mixture is not available. Expected to be an irritant

based on components. Irritating to eyes. May cause redness, itching, and pain. May cause

temporary eye irritation.

Skin Contact Specific test data for the substance or mixture is not available. Expected to be an irritant

based on components. Irritating to skin. Prolonged contact may cause redness and

irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Silica 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 2.2 mg/L (Rat)1 h
Carbon black 1333- 86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-



Silicone Sealant – Oxime - Grey

Revision Date 30-Apr-2015

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes.

Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin

contact. May cause sensitization by inhalation.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Silica 7631-86-9		Group 3		
Carbon black 1333- 86-4	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic Toxicity

No known effect based on information supplied. Contains a known or suspected

carcinogen. Carbon black has been classified by the International Agency for Research

on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Lymphatic System. Lungs.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

11,500.00 mg/kg



12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Silica 7631-86-9	72h EC50: = 440 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 5000 mg/L (Brachydanio rerio)		48h EC50: = 7600 mg/L
Carbon black 1333-86-4				24h EC50: > 5600 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methodsThis material, as supplied, is not a hazardous waste according to Federal regulations (40)

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional,

or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT NOT REGULATED
Proper Shipping Name NON REGULATED

Hazard Class N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

Not regulated

IATA
Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

RID Not regulated

ADR Not regulated

ADN Not regulated



15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Carbon black - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

.Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Limestone 1317- 65-3	Х	Х	X		
Silica 7631-86-9		Х	Х		
Carbon black 1333- 86-4	X	Х	X		X



International Regulations

Mexico National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Limestone 1317-65-3 (30 - 60)		Mexico: TWA= 10 mg/m ³ Mexico: STEL= 20 mg/m ³
Carbon black 1333-86-4 (1 - 5)		Mexico: TWA 3.5 mg/m ³ Mexico: STEL 7 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class

D2B - Toxic materials



16. OTHER INFORMATION					
NFPA	Health Hazards 2	Flammability 0	Instability 0	Physical and Chemical Hazards -	
HMIS	Health Hazards 2	Flammability 0	Physical Hazard 0	Personal Protection	

Prepared By
Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

1-800-572-6501 15-Oct-2014

Revision Note No information available

Disclaimer

Revision Date

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

