

Product Description:

Pro-Seal Nano ISO Component remover is used with Pro-Seal DC 1.3 Nano ISO Polyfoam re-mover. Pro-Seal ISO Component Remover is used only to remove unmixed raw ISO from concrete or other approved substrates. Pro-Seal Nano ISO Component Remover breaks down the matrix of ISO at the nano level reverting it to a gel, for ease of removal.

Features:

Pro-Seal ISO Component Remover is:

- Fast acting typically removes stains in less than fifteen minutes from concrete.
- Spray on or pour on.
- Minimizes labors cost.
- Reduces cost per square foot of removal dramatically.
- No special skill required.

Advantages

Pro-Seal ISO Component Remover is:

- No more grinding and patching concrete.
- No more removal and replacing concrete.
- Happy clients.
- One and done, in and out.
- Reduces mobilizations and demobilizations.

Benefit

Pro-Seal ISO Accelerator is:

- A more professional approach.
- Helps reduce liability.
- Helps protect project profits.
- Happier clients.
- Happier you.



Yellow ISO component spot.



Spray apply DC 1.3 applied and scrub, let stand 3 to 5 minutes.



Spray apply Pro-Seal ISO Component Remover directly to the surface pretreated with Pro-seal DC 1.3 target spot. Scrub until it gels, power rinse off.



1 hour later yellow staining gone still damp. Note: some light shadowing may occur in stains older than 48 ours or under unique site specific conditions. Some shadowing may be present in porous substrates.

Basic Application:

1. Pour or spray Pro-Seal DC 1.3 onto the affected concrete as appropriate.
2. Allow Pro-Seal DC 1.3 to sit resident for 5 to 6 minutes.
3. Lightly scrub the treated area with stiff brush.
4. Spray ISO Component Remover onto treated stain.
5. Allow to stand 3 to 5 minute
6. Lightly scrub treated area with stiff brush until the brush strokes appear in the gel that forms.
7. Power rinse/wash effected area; rinse with clean tap water.
8. Collect removed residue with water vacuum and dispose of residue per city, county, state and federal regulations

Contact Technical

Call USA CN: 1 800 349 7325 +1 206 451 9527
Email: information@prosealproducts.com

Contact Information:

Call USA/CN: 800 349 7325 or Int'l +1 206 451 9527

Email: information@prosealproducts.com Web: prosealproducts.com



**Yellow ISO
Stain
Before.**



**1 Hour Later
After Removal
(Still Wet)**

Removing ISO Stains

Pro-Seal Nano ISO Component Remover to remove ISO stains must be used with Pro-Seal DC 1.3 Nano ISO Poly foam Stain Remover to be effective. For best and quickest results, stains must be under 36 hours old. To request a typical use general instructions video please contact pro-seal Products Technical Department at:

Call USA CN: 1 800 349 7325 +1 206 451 9527
Email: information@prosealproducts.com

Shipping and Handling Placards:

Flammable, Health Hazard, Aggressive towards plastics and rubber. Mild Cos-tic. Keep away from open flame or hea-ters and NO SMOKING. Keep away from children and non-professionals.



Storage: Store in supplied lined metal container per fire department regulations. Do not reuse container.

Warning: Flammable, Health Hazard, Aggressive towards plastics and rubber. **Milde Costic, and No Smoking.**

Safety:



Wear required personal protective safety equip-ment examples: head gear, eyewear, clothing, appropriate ventilation or respirator, and foot-wear as required by federal, state, or local regulations. See SDS for details.

Cautions:

Keep out of reach of children. May cause skin or eye irritation. Rinse with water any skin contact areas. This product may be harmful if swallowed. Do not induce vom-iting. Use in well-ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applica-tions. Use only on intended surfaces. Con-tact manufacturer for specific application uses. See materials, safety data sheet for additional cautions.

Limited Warranty:

We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations made herein are based upon information we believe to be dependable; however we make them without any representation, guarantee, or warranty of accuracy. Pro-Seal sold by the seller, to the purchasers, under the con-dition that the purchasers themselves will evaluate the product and our recom-mendations, to determine if there is suit-ability for the user's own purpose and use, before adoption of the use of our products. Additionally, statements made by anyone regarding the use of our products and/or processes shall not to be construed, by the buyer and/or user, as recommendations for the users' adoption of use, in violation of any patent rights or in violation of any applicable laws, codes, or regu-lations. The manufactures liability, under any condition, shall-be-limited-to-the replacement of material only and only that portion of material proven to have failed under manufactures parameters.



Contact Information:

Call USA/CN: 800 349 7325 or Int'l +1 206 451 9527

Email: information@prosealproducts.com Web: prosealproducts.com