

Pro-Seal DeGraf™ graffiti remover



Removes graffiti effortlessly when used with Pro-Seal AntiGraf no- sacrificial graffiti barrier system.

Pro-Seal DeGraf™ graffiti remover is the alternative to environmentally unsound aggressive solvents. Extracted from natural citrus rind and blended with biodegradable, nano detergents, and emulsifiers. Pro-Seal DeGraf™ floats most graffiti off Pro-Seal AntiGraf protected surfaces effortlessly. Pro-Seal DeGraf will remove the vast majority of taggers medium off of most natural surfaces with ease.

- Spray on graffiti melts off.
- Biodegradable
- Phosphate Free
- It's Green
- V.O.C. Compliant
- Can be used with DP-36® to extract deep saturated fluid contaminants from concrete substrates.

Benefits

- Easy to apply and use, just spray.
- Removes most taggers graffiti mediums.
- Makes Pro-Seal AntiGraf graffiti barrier non sacrificial.
- Removes graffiti from sealed and unsealed surfaces.

Applications: Concrete, Stone, Brick, Marble, Metal, CMU Block and more.

Application Instructions

1. Apply at an average coverage rate of 300 square feet per gallon.
2. Agitate the surface using a stiff bristled brush or broom.
3. Rinse surface and remove debris per local, state, and federal regulation.
4. For specific application instructions or guide specifications, contact Pro-Seal's Technical Department at 800.349.7325 or information@prosealproducts.com

**Always apply a test patch before use. Do not use on rubber or hydrocarbon based surfaces that are not intended to be removed or destroyed.*

Technical

Information	Value
Material	1 Part
Appearance	Liquid
Application Temp	> 40°F
Storage Temp	< 100°F
Flammability	None
Odor	Citrus
Packaging	Quart, 1, 5, and 55 gallons

Technical Support: Contact technical department at 800.849.7325, information@prosealproducts.com or visit our website www.prosealproducts.com for additional information.

Cautions: Keep out of reach of children. May cause skin or eye irritation. The product could be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty: We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.



16541 Redmond Way • Suite 363C • Redmond, WA 98052
Phone: 800.349.7325 • information@prosealproducts.com
www.prosealproducts.com • © Copyright Pro-Seal