

# Pro-Seal Flash Guard Tape™

Polycarbon/Polycarbonate Peel-and-Stick Flashing Tape



**Flash Guard Tape™** is a single component peel-and-stick sealer that is supplied as a rolled-good.

*\*Polycarbon/polycarbonate integrated technology.*

- Easy to install use with Pro-Seal 34 in flashing system
- Provides Instant grip to a large variety of substrates
- Easily cut into any shape or length
- Fleece backing for coating, sealer or membrane adhesion
- Self-adhering
- Seals on contact
- Conforms to almost any shape

**Applications:** Flash, cracks, Joints, Penetrations, Pipes, Parapet walls, Roofing, HVAC ductwork, Flashings, Railways, Metal roofs, through holes and more.

**Application Instructions:** Surface must be dry, clean and free of all loose particulate and bond-breaking matter. For specific application instructions or guide specifications, contact Pro-Seal's Technical Department at 800.349.7325 or [information@prosealproducts.com](mailto:information@prosealproducts.com)

## Technical

Information	Value
Material	1 Part
Mix Time	N/A
Appearance	Rolled-Good
Application Temp.	35°F To 220°F
Service Temp.	-20°F To 180°F
V.O.C.	None
Flash Point	N/A
Tensile Strength	570 psi
Peel Strength	10 lbs / Linear Inch
Color	White & Gray
Solids	100%
Packaging:	4" X 50' Roll, 6" X 50' Roll or 12" X 50' Roll

**Technical Support:** Contact our technical department at 800.349.7325, [information@prosealproducts.com](mailto:information@prosealproducts.com) or visit our website [www.prosealproducts.com](http://www.prosealproducts.com) for additional information.

**Cautions:** Keep out of reach of children. May cause skin or eye irritation. This product may be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.



Pro-Seal Flash Guard Tape® (Pro-Seal 34® caulking sealant material applied to a fleece backing for ease of flashing application) is used with Pro-Seal 34® caulking to create a flashing seal that has mobility and flexibility to avoid flashing failure.

Pro-Seal 34® is first applied to joints, cracks surface transition or other movement anomalies just prior to placing Pro-Seal FlashGuard Tape® on center over the Pro-Seal 34® when placing a Pro-Seal® seamless waterproofing or contaminant resistant membrane coating.



16541 Redmond Way • Suite 363C • Redmond, WA 98052  
Phone: 800.349.7325 • [information@prosealproducts.com](mailto:information@prosealproducts.com)  
[www.prosealproducts.com](http://www.prosealproducts.com) • © Copyright Pro-Seal