

Pro-Seal 34® It's The good stuff

Caulking for Wet or Damp Environments



Applying Through Running Water

Pro-Seal 34® sticks to every known surface except a bar of soap!

- Seals through rain, moving water and lubricants
- Never gets hard or brittle
- 1200% elongation
- 350% stretch
- 2-year shelf life
- 6-month open tube life
- Paintable upon application
- Potable water certified

Where to use:

Recreational Vehicles	Window Flashings
Automotive Lights	All Penetrations
Eyebrow Flashings	Chimney Flashings
Edge Flashings	Joint Overlaps
Garden Windows	Plastic-Metal Seals

Covered seals under water:

Pools	Hot tubs	Boats
-------	----------	-------

Around the house:

Roofing	Sky lights	Vents
Flashings	Plumbing	Gutters
Deck Drains	HVAC Ducts	Drains
Roof Patch	Scuppers	Flashings
Down Spouts	Deck lights	Windows
Boat Portholes and more...		



The Pro-Seal ProGun® will make it easier to get into those tight and difficult to reach sealing spaces.

Available in five (5) colors:

- | | |
|-----------------------|---------|
| • Clear (glass clear) | • White |
| • Grey | • Black |
| • Anodized Brown | |



16541 Redmond Way • Suite 363C • Redmond, WA 98052
Phone: 800.349.7325 • information@prosealproducts.com
www.prosealproducts.com • © Copyright Pro-Seal

Pro-Seal 34® It's The good stuff

Caulking for Wet or Damp Environments



Coverage

Joint size	Linear Feet / Tube
1/8"x1/8"	106.4
1/8" x 1/4"	53.2
1/8" x 3/8"	35.4
1/8" x 1/2"	26.6
1/8" x 5/8"	21.3
1/8" x 3/4"	17.7
1/8/ x 7/8"	15.2
1/8" x 1"	13.3
1/4" x 1/4"	26.6
3/8" x 3/4"	6.0
3/8" x 7/8"	5.1
3/8" x 1"	4.4
1/2" x 1/2"	6.7
1/2" x 5/8"	5.4
1/2" x 3/4"	4.4

Technical Support: Contact our technical department at 800.349.7325, information@prosealproducts.com or visit our website www.prosealproducts.com for additional information

Cautions: Keep out of reach of children. May cause skin or eye irritation. This product may be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions. Do not run beads greater than 1/2" x 1/2" per application. In joints where greater bead size is required, multiple applications will be necessary. If



gassing breaks or cracks occur, simply remove particulate or dirt and apply more Pro-Seal 34® as it adheres to itself. Shelf life is based on the date of manufacturer of batch number.

NSF 61 certified for use with potable water request data from technical 800 349 7325.

LARR Number 20015 certified for use with methane barriers. Request data from technical 800 349 7325.

For ASTM Data see TDS or request from technical 800 349 7325.

For Fed Spec Data see TDS or request from technical 800 349 7325.

Pro-Sal 34 Is LEEDS, Redline, GoGreen Compliant

Pro-Seal 34 caulking sealant, the right stuff, the stuff works, to make environmental positive impact, just use it.

Limited Warranty:

We warrant our product to be free of defects in material and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.

Distributed by: