

PRODUCTS, INC.

Pro-Seal 34 seals under water, through oil and adheres with no primer. It has no memory, even when fully cured.

- Roof seams (Fiberglass and Rubber) • Roof gutters • Sunroof & Skylight
- Antennas & Satellites • HVAC Units • Horns/Air Horns • Rails & Ladders
- Exhaust Vents (Bathroom) • Galvanized metal • Aluminum • Vinyl • Remains flexible
- Seals through rain and moving water • Two year shelf life • Six month open tube life
- 350% Stretch • 1200% Elongation
- Paintable upon application
- Non-yellowing from UV rays

** Not intended for bathrooms in exposed or traffic areas*



- Membrane Sheet Roof front and back seams
- Water heater outer edges, helps with insulation
- Any other roof accessories that are bolted on the roof membrane
- Fiberglass or Rubber roofs with cracks or tears, excellent for sealing
- No negative effect on the Type II foam insulation

Perfect for fixing OEM Roof Seals, Window Trim Seals and Leaking Areas

Pro-Seal 34 is a single component M34 elastoplastic, polycarbon/polycarbonate sealant material. Stops leaks and seals on contact even through water and oil. Pro-Seal 34 is gunable from 38°F to 98°F and may be applied to surface temperatures ranging from -70°F to +220°F.

