

Pro-Seal R.O.C. Hard™

Non-Solvent Surface Hardening & Polishing Agent



Product Description:

R.O.C. Hard™ is a single component concrete hardening agent. This product cures and polishes concrete to a high shine “Rock Hard” finish. **Polycarbon/polycarbonate integrated technology.*

Features:

- Non-solvent
- Increases hardness up to 21%
- No V.O.C.
- Meets or exceeds USDA standards for food areas
- Moisture resistant

Applications on Concrete:

- Retail Floors
- Commercial Building Floors
- Warehouse Floors
- Commercial Kitchen Floors
- School floors
- Countertops

and more.

Application:

Surface must be clean and free of all loose particulate and bond-breaking matter. For specific application instructions or guide specs, contact us at 800.349.7325 or information@prosealproducts.com

Technical Support:

Contact our technical department at 800.349.7325, information@prosealproducts.com or visit our website www.prosealproducts.com for additional information

Technical

Information	Value
Material	1 part
Mix time	None
Appearance	Liquid
V.O.C. content	N/A
Flash point	230°F
Cure time to touch	45 minutes
Cure time complete	2 hours
Stain resistance	N/A
Penetrates	1-22 mils
Specific gravity	8.46
Packaging:	1, 5 and 55 gallon

Specifications

Test	Data	Value
Water absorption	Low air content	.08%
Water absorption	Normal air content	.14%
ASTM C 156 AASHTO M-155	Significant improvement in curing against hairline cracking due to shrinkage	X 100p negative to zero
ASTM C 672	Freeze thaw	No damage
ASTM C 672	Ambient	7%
ASTM C 672	@ 2.45 cm chloride content	1.5%
ASTM C 672	@ 2.45 cm non air entrained	1.8%
ASTM C 672	@ 2.45 cm air entrained	7%
Brookfield viscometer	Viscosity	> 5,000 cps
ASTM 2369-92	V.O.C. content	None

* Data based on laboratory tested materials.



Pro-Seal R.O.C. Hard® commercial concrete floor hardener. Easy to apply with a commercial floor scrubber.



16541 Redmond Way • Suite 363C • Redmond, WA 98052
Phone: 800.349.7325 • information@prosealproducts.com
www.prosealproducts.com • © Copyright Pro-Seal

Pro-Seal R.O.C. Hard™

Non-Solvent Surface Hardening & Polishing Agent



Pro-Seal R.O.C. HARD®

- Step 1.** Clean Concrete floor Remove all mastics, Glues debris and other non concrete barrier materials
- Step 2.** Wet Prepared Concrete Floor with Clean Tap Water and apply Pro-Seal DP-36
- Step 3.** Wet Floor with Pro-Seal R.O.C. Hard at the recommended coverage rate for site
- Step 4.** Burnish Pro-Seal ROC Hard into floor with a floor scrubber or a diamond grinder per guide specification
- Step 5.** Rise and squeegee excesses off floor allow to dry about 1 hour to service ready

Application Step by Step

WHOLE FOODS

MASON'S CAFE



Commercial floors

Cautions:

Keep out of reach of children. May cause skin or eye irritation. This product may be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty:

We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.



Retail Floors



Warehouse floors