



CLUB CAR DS CARGO BOX INSTALLATION INSTRUCTIONS

MJCBB1001

INCLUDED:

- 2 BRACKETS
- 2 BAGWELL BRACKETS
- 3 HARDWARE PACKS



1
Remove hardware from canopy. Retain hardware you will need it later. Remove canopy from golf cart.



2
Take off the front seat by removing the hardware located behind the seat. Retain hardware. You will need it later.



Remove front basket hardware. Retain all hardware. You will need it later.

3

Remove motor cover panel. Retain hardware. You will need it later.

4




Remove rear basket hardware. Access hardware from inside motor compartment. Retain hardware. You will need it later.

5



Attach main bracket to golf cart using retained hardware from step 3.

6





Remove hardware from rear bumper. You do not have to completely remove the bumper from the golf cart.

Attach bagwell brackets to bumper using retained hardware from step 6. Place main brackets on golf cart and attach to bagwell brackets using hardware from pack 1.



Attach front seat to brackets using hardware retained from step 2.

Install rear struts using hardware from pack 2.





Place the cargo box on the brackets and align holes. Using hardware from pack 3, insert all bolts into box and then tighten.



Reinstall canopy by placing it on the struts and reattaching hardware from step 1.

CLUB CAR DS CARGO BOX HARDWARE PACKS

HARDWARE PACK 1

BUMPER BRACKETS TO BOX BOX BRACKETS

- (2) 10MM X 40MM SHOULDER HEX BOLTS**
- (4) 10MM X 25MM X 2MM WASHERS**
- (2) 10MM ANTI-SLIP NUTS**

HARDWARE PACK 2

REPLACES FACTORY REAR STRUT HARDWARE

- (4) 6MM X 45MM SHOULDER HEX BOLTS**
- (8) 6MM X 18MM X 2MM WASHERS**
- (4) 6MM ANTI-SLIP NUTS**

HARDWARE PACK 3

CARGO BOX

- (4) 10MM X 25MM SHOULDER HEX BOLTS**
- (8) 10MM X 25MM X 2MM WASHERS**
- (4) 10MM ANTI-SLIP NUTS**