



- GENERAL NOTES:**
- FALL THROUGH HYDRO-KINETIC® PLANT FROM INLET INVERT TO OUTLET INVERT IS FIVE INCHES.
 - ON DEEPER INSTALLATIONS, RISERS MUST BE USED TO EXTEND TANK RISERS TO GRADE. INSPECTION COVER ON PRETREATMENT CHAMBER MUST BE DEVELOPED TO WITHIN TWELVE INCHES OF GRADE.
 - REMOVABLE COVERS ON RISERS ARE EACH SECURED TO PREVENT UNAUTHORIZED ACCESS.
 - CONTACT THE LOCAL, LICENSED HYDRO-KINETIC® DISTRIBUTOR FOR ELECTRICAL REQUIREMENTS.
 - AIR PUMP MAY BE MOUNTED INSIDE THE RISER ABOVE THE AERATION CHAMBER OR MAY BE REMOTE MOUNTED UP TO 100 FEET FROM TANK.

PROJECT ENGINEER'S APPROVAL:
I (WE) HEREBY CERTIFY THAT THIS DRAWING HAS BEEN CHECKED AND IS APPROVED.

DATE: _____
NAME: _____

CONTRACTOR'S CERTIFICATION:
I (WE) HEREBY CERTIFY THAT THIS DRAWING HAS BEEN CHECKED AND IS APPROVED.

DATE: _____
NAME: _____

CRITICAL DIMENSIONS

A	3'- 3"	N	0'- 0 3/8"
B	3'- 5 1/4"	O	0'- 6"
C	4'- 2 1/4"	P	0'- 0 3/8"
D	4'- 2 1/4"	Q	1'- 3 1/2"
E	2'- 8 3/4"	R	4'- 2 1/2"
F	14'- 9 1/2"	S	5'- 6"
G	0'- 10 1/2"	T	1'- 4"
H	4'- 7 1/2"	U	6'- 6"
I	0'- 4"	V	5'- 5"
J	0'- 1 1/2"	W	
K	1'- 0"	X	
L	0'- 0 3/4"	Y	
M	4'- 3"	Z	

U.S. AND FOREIGN PATENTS PENDING	norweco	REVISION DATE: 09-07-2017	REVISION: B
	HYDRO-KINETIC® GREEN 600 FEU WASTEWATER TREATMENT SYSTEM	APPROVED BY: JMM	DATE: 11-18-2014
© MMXVII		SCALE: NTS	DRAWING NO: PC-S-1055

NOTE: TOTAL SYSTEM CAPACITY: 1,785 GALLONS
RATED CAPACITY: 500/600 GALLONS PER DAY