

Temperature transmitter with dual channels and configuring, backlit, optical display feature.

RTT15S

## Main

Range of Product	Temperature	
Product or Component Type	Temperature transmitter	
Type of Measurement	Temperature	
Market Segment	Oil and gas Paper and pulp Chemical Pharmaceutical	

# Complementary

Measurement accuracy	+/- 0.5 °C with thermocouple K +/- 1 °C with RTD PT100	
Communication port protocol	HART, 420 mA	
Network and machine diagnosis type	Sensor broken Sensor shorted	

## **Environment**

Standards	DIN
Ambient air temperature for operation	-40185 °F (-4085 °C) -4085 °C (-40185 °F)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### **Use Better**

Materials and Substances	
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### **Use Again**

○ Repack and remanufacture	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.