## SAFETY DATA SHEET



### 1. Identification

Product identifier BEHR Water-Based Fast-Drying Polyurethane Satin

Other means of identification

Product code B8100

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

**Supplier** Behr Process Corp.

1801 E. St. Andrew Place Santa Ana. CA 92705

 Telephone
 714-545-7101

 Emergency telephone
 +1 760 476 3962

+1 866 519 4752

Access code 335213

### 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

**Hazard statement** The mixture does not meet the criteria for classification.

**Precautionary statement** 

**Prevention** Observe good industrial hygiene practices.

Response Wash hands after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
Paraffin waxes and Hydrocarbon waxes	8002-74-2	1 - 3

Composition comments The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard

Communication Standard.

4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

BEHR Water-Based Fast-Drying Polyurethane Satin

951036 Version #: 00 Revision date: 11-25-19 Issue date: 11-25-19

1 / 6

Most important symptoms/effects, acute and

delayed

Treat symptomatically.

Indication of immediate medical attention and special

treatment needed **General information** 

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Direct contact with eyes may cause temporary irritation.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapors. Avoid prolonged exposure. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

### Occupational exposure limits

### **US. ACGIH Threshold Limit Values**

Components	Туре	Value	Form	
Paraffin waxes and	TWA	2 mg/m3	Fume.	
Hydrocarbon waxes (CAS				

# **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	туре	value	1 01111	
Paraffin waxes and	TWA	2 mg/m3	Fume.	
Hydrocarbon waxes (CAS				

**Biological limit values** 

8002-74-2)

8002-74-2)

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Value

Form

BEHR Water-Based Fast-Drying Polyurethane Satin SDS US 2/6 951036 Version #: 00 Revision date: 11-25-19 Issue date: 11-25-19

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

If airborne concentrations are above the applicable exposure limits, use NIOSH approved Respiratory protection

respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. **Form** Liquid. Milky. Color Odor Slight.

Odor threshold Not available.

7 - 10 pН

Not available. Melting point/freezing point Initial boiling point and boiling > 99 °F (> 37.2 °C)

range

Flash point Not applicable. **Evaporation rate** Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Vapor pressure Vapor density

Not available. Not available. Not available.

Relative density Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available.

15 - 40 (Seconds, #3 Zahn Cup) Viscosity

Other information

Density 8.43 lb/gal **Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

VOC 73 g/l (including water)(Material) 199 g/l (excluding water)(Coating)

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport. Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid**Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

### 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Prolonged skin contact may cause temporary irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

#### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Skin corrosion/irritationProlonged skin contact may cause temporary irritation.Serious eye damage/eyeDirect contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed

### NTP Report on Carcinogens

Not listed.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

#### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil

Other adverse effects

No data available.

No data available.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

BEHR Water-Based Fast-Drying Polyurethane Satin

951036 Version #: 00 Revision date: 11-25-19 Issue date: 11-25-19

4 / 6

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

#### 15. Regulatory information

**US** federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

### **US state regulations**

**US. Massachusetts RTK - Substance List** 

Paraffin waxes and Hydrocarbon waxes (CAS 8002-74-2)

US. New Jersey Worker and Community Right-to-Know Act

Paraffin waxes and Hydrocarbon waxes (CAS 8002-74-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Paraffin waxes and Hydrocarbon waxes (CAS 8002-74-2)

**US. Rhode Island RTK** 

Paraffin waxes and Hydrocarbon waxes (CAS 8002-74-2)

### 16. Other information, including date of preparation or last revision

Issue date Draft version.

BEHR Water-Based Fast-Drying Polyurethane Satin SDS US 5/6 951036 Version #: 00 Revision date: 11-25-19 Issue date: 11-25-19

Revision date 11-25-19
Version # 11-25-19
HMIS® ratings Health: 0

Flammability: 0 Physical hazard: 0

**List of abbreviations** LD50: Lethal Dose, 50%.

DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

MARPOL: International Convention for the Prevention of Pollution from Ships.

TWA: Time Weighted Average Value.

References HSDB® - Hazardous Substances Data Bank

**Disclaimer** Behr Process Corp cannot anticipate all conditions under which this information and its product, or

Issue date: 11-25-19

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

BEHR Water-Based Fast-Drying Polyurethane Satin 951036 Version #: 00 Revision date: 11-25-19

SDS US

6/6