

## WPSM800000L

## BLACK WATER BASED SOFT-MATT ENAMEL

Descriptive notes					el formulat the touch		th specia	l resin	s and a	additives	with	excellent s	surface
Gloss Versions		3 - 5											
USAGE													
Suitable for	Cabinet doors		Furniture		Artisans								
Method of application	Spray		Air m spray	ixing painting	Automatic spraying								
MAIN PROPERTIES													
							Yellowi	ng Res	istance			High	
					7	Scratch Resistance			High				

## PREPARATION OF THE PRODUCT

PREPARATION OF THE PRODUCT					
	Code	%	Descriptive notes		
Recommended thinner	water	10 - 15	Add after mixing of the hardener		
Other thinners					
Recommended hardener	INUR0600	15	Mix with a low / medium speed mechanical stirrer		
Other hardeners					
Accelerant.					

CHEMICAL-PHYSICAL CHA	RACTERISTICS	APPLICATION CHAR	ACTERISTICS	DRYING		
Specific gravity (kg/l) ±0.03	1,05	N° of coats	1	Dust free (min)	40	
Solids Content (%) ±1	39	Qty. per coat (g/m²)	120 - 130	Touch dry (min)	120	
Viscosity DIN 4 (20°C)	55" - 65"					
Pot-Life at 20°C ( h )	> 2					

Additional information:

The product is formulated only in opacity shown above. To obtain a perfect uniformity of opacity, oven-dry at 40  $^{\circ}$  C after the dust-free time.

## WARNING

Our data sheets are drawn up on the basis of average results of our trials. However our tech tips are given in good faith but without guarantee. In fact, several media, conditions of application, plant and dilutions are an integral part of the final result and often beyond our control. The user must try the products supplied to test whether suitable to your needs. For our part we guarantee the continuity of the chemical-physical characteristics.

Warning: it is the user's responsibility to provide that the application is in properly ventilated environment hygienic and in accordance with standards and accident prevention regulations currently in force.

Revision n° 2 Revision 14/01/20 Date 20	Printed: 14/01/2020
---	---------------------